




**ENERG**  
енергия · ενεργεια

Y IJA  
IE IA



Indoor unit E\*ST30D-\*\*\*\*D  
Outdoor unit PUZ-SHWM100YAA



A+++

A++

A+

A

B

C

D

A++

A+

A

B

C

D

E

F

A+

41 dB

58 dB



- 10 kW
- 10 kW
- 10 kW

2019

811/2013

DG79V341H32



PRODUCT FICHE

Mitsubishi Electric Erp Directive Related Product Information: erp.mitsubishielectric.eu/erp
Details and precautions on installation, maintenance and assembly can be found in the installation and/or operation manuals.
This information is based on EU regulation No 811/2013 and No 813/2013.

DG79A02MH01

Table 1: SPACE HEATER. Columns: Outdoor unit, Indoor unit, Medium-temperature application (3-25), For low-temperature application (4-25). Rows: PUZ-SWM60VAA, PUZ-SWM80VAA, PUZ-SWM80YAA, PUZ-SWM100VAA, PUZ-SWM100YAA, PUZ-SWM120VAA, PUZ-SWM120YAA, PUZ-SWM140VAA, PUZ-SWM140YAA, PUZ-SWM80VAA, PUZ-SWM80YAA, PUZ-SWM100VAA, PUZ-SWM100YAA, PUZ-SWM120VAA, PUZ-SWM120YAA, PUZ-SWM140VAA, PUZ-SWM140YAA.

Table 2: COMBINATION HEATER. Columns: Outdoor unit, Indoor unit, Medium-temperature application (3-25), For low-temperature application (4-25). Rows: PUZ-SWM60VAA, PUZ-SWM80VAA, PUZ-SWM80YAA, PUZ-SWM100VAA, PUZ-SWM100YAA, PUZ-SWM120VAA, PUZ-SWM120YAA, PUZ-SWM140VAA, PUZ-SWM140YAA, PUZ-SWM80VAA, PUZ-SWM80YAA, PUZ-SWM100VAA, PUZ-SWM100YAA, PUZ-SWM120VAA, PUZ-SWM120YAA, PUZ-SWM140VAA, PUZ-SWM140YAA.

English	Deutsch	Franglais	Italiano	Espanol
Nederlands	Svenska	Dansk	Portugals	Ελληνικά
suomi	Čeština	Български	Polski	Ελληνικά
Outdoor unit	Außengerät	unité extérieure	unita esterna	unidad exterior
1	Ulmohäsmet	Uleniders enlid	unidad exterior	Εξωτερική μονάδα
Ulkokeskus	Vonkumil jatkoka	Външни тло	república zewnątrzlo	υπομονή
2	Indoor unit	unité intérieure	unita interna	unidad interior
Sisäyksykki	Innenset	Вътрешно тло	interna interior	Εσωτερική μονάδα
3	Medium-temperature application	l'application à moyenne température	република w średniej temperaturze	la aplicación de media temperatura
keskilämpötilan sovellus	mittitemperatuuriläpikäyttö	middletemperatuuriläpikäyttö	republica w średniej temperaturze	la aplicación de media temperatura
4	Low-temperature application	Niedertemperaturanwendung	l'application à basse température	la aplicación de baja temperatura
alipääntemperatuurin sovellus	Niedertemperaturanwendung	l'application à basse température	republica w niskiej temperaturze	la aplicación de baja temperatura
5	Deelgedeelte van de rolle	Агрегативен част от роля	Profil de service de rôle	Perfil de servicio de rollo
Srbeleven serviceforhold	Delkødet af betjeningsforhold	Агрегативен част от роля	Profil de service de rôle	Perfil de servicio de rollo
6	Seasonal space heating energy efficiency class	la classe d'efficacité énergétique saisonnière	la classe d'efficacité énergétique saisonnière	la clase de eficiencia energética estacional
de sæsonreguleret energieffektivitetsklasse	la classe d'efficacité énergétique saisonnière	la classe d'efficacité énergétique saisonnière	la classe d'efficacité énergétique saisonnière	la clase de eficiencia energética estacional
7	Water heating energy efficiency class	la classe d'efficacité énergétique pour le chauffage de l'eau	la classe d'efficacité énergétique pour le chauffage de l'eau	la clase de eficiencia energética del calentamiento de agua
de energiefølelighed for vandvarmning	la classe d'efficacité énergétique pour le chauffage de l'eau	la classe d'efficacité énergétique pour le chauffage de l'eau	la classe d'efficacité énergétique pour le chauffage de l'eau	la clase de eficiencia energética del calentamiento de agua
8	Rated heat output under average climate conditions	l'efficacité énergétique nominale dans les conditions climatiques moyennes	l'efficacité énergétique nominale dans les conditions climatiques moyennes	la potencia calorífica nominal (en condiciones climáticas medias)
de nominale varmeafgivelse (under gennemsnitlige klimaatbetingelser)	Den nominale varmeafgivelse (under gennemsnitlige klimaatbetingelser)	l'efficacité énergétique nominale dans les conditions climatiques moyennes	l'efficacité énergétique nominale dans les conditions climatiques moyennes	la potencia calorífica nominal (en condiciones climáticas medias)
9	For space heating, annual energy consumption under average climate conditions	For die Raumlheizung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen	For die Raumlheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
tila mittimääräistä lämmitystä ilmasto-olosuhteissa	For die Raumlheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	For die Raumlheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
10	For water heating, annual electricity consumption under average climate conditions	For die Warmwasserbereitung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen	For die Warmwasserbereitung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias
voor waterverwarming, het jaarlijkse elektriciteitsverbruik (onder gemiddelde klimaatomstandigheden)	For waterverwarming, het jaarlijkse elektriciteitsverbruik (onder gemiddelde klimaatomstandigheden)	For waterverwarming, het jaarlijkse elektriciteitsverbruik (onder gemiddelde klimaatomstandigheden)	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias
11	Seasonal space heating energy efficiency under average climate conditions	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción espacial en condiciones climáticas medias
de sæsonreguleret energieffektivitet (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción espacial en condiciones climáticas medias	la eficiencia energética de calefacción espacial en condiciones climáticas medias
12	de energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias
vedelämmityksen energiefølelisuus (keskimääräisissä ilmasto-olosuhteissa)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias	la eficiencia energética de calefacción en condiciones climáticas medias
13	Sound power level L <sub>WA, indoor</sub>	den Schalleistungspegel L <sub>WA, in Gebäuden</sub>	el nivel de potencia acústica L <sub>WA, en interiores</sub>	la potencia acústica L <sub>WA, en interiores</sub>
het geluidsemissievermogen L <sub>WA, binnen</sub>	den Schalleistungspegel L <sub>WA, in Gebäuden</sub>	el nivel de potencia acústica L <sub>WA, en interiores</sub>	el nivel de potencia acústica L <sub>WA, en interiores</sub>	la potencia acústica L <sub>WA, en interiores</sub>
14	Werkten uitvoerend in de dalen	hidralna akustičko ukupno L <sub>WA, ve vlnitnom prostoru</sub>	hidralna akustičko ukupno L <sub>WA, po mjestu</sub>	hidralna salomita durante las horas de baja demanda
Werkten uitvoerend in de dalen	hidralna akustičko ukupno L <sub>WA, ve vlnitnom prostoru</sub>	hidralna akustičko ukupno L <sub>WA, po mjestu</sub>	hidralna salomita durante las horas de baja demanda	hidralna salomita durante las horas de baja demanda
15	kommaan antoosam kuluksiturvallisen ulkoruokailu	provozu ručeje tamo spruku	работи само в часовете наван вхрвова неговарване	la potencia calorífica nominal en condiciones climáticas medias
Rated heat output under colder climate conditions	die Wärmeleistung bei kaltem Klimaverhältnissen	работи само в часовете наван вхрвова неговарване	работи само в часовете наван вхрвова неговарване	la potencia calorífica nominal en condiciones climáticas medias
de nominale warmteafgifte (onder kouder klimaatomstandigheden)	Normaal leveren warmteafgifte uit kalere klimaatomstandigheden	работи само в часовете наван вхрвова неговарване	работи само в часовете наван вхрвова неговарване	la potencia calorífica nominal en condiciones climáticas medias
l'efficacité nominale (sous conditions climatiques moins chaudes)	Normaal leveren warmteafgifte uit kalere klimaatomstandigheden	работи само в часовете наван вхрвова неговарване	работи само в часовете наван вхрвова неговарване	la potencia calorífica nominal en condiciones climáticas medias
16	Rated heat output under warmer climate conditions	de Wärmeleistung bei wärmerem Klimaverhältnissen	la puissance thermique nominale dans les conditions climatiques plus chaudes	la potencia calorífica nominal en condiciones climáticas medias
de nominale warmteafgifte (onder warmere klimaatomstandigheden)	Normaal leveren warmteafgifte uit wärmer Klimaverhältnissen	la puissance thermique nominale dans les conditions climatiques plus chaudes	la puissance thermique nominale dans les conditions climatiques plus chaudes	la potencia calorífica nominal en condiciones climáticas medias
17	For space heating, annual energy consumption under colder climate conditions	proyektiruyemyy godovoye potrobleniye pri postoyannykh klimaticheskikh usloviyakh	nominalnaya toplinaya moyshnost' pri postoyannykh klimaticheskikh usloviyakh	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
voor ruimteverwarming, het jaarlijkse energieverbruik onder koudere klimaatomstandigheden	For die Raumlheizung, der jährliche Energieverbrauch bei kaltem Klimaverhältnissen	nominalnaya toplinaya moyshnost' pri postoyannykh klimaticheskikh usloviyakh	nominalnaya toplinaya moyshnost' pri postoyannykh klimaticheskikh usloviyakh	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
18	For space heating, annual energy consumption under warmer climate conditions	For die Raumlheizung, der jährliche Energieverbrauch bei wärmerem Klimaverhältnissen	For die Raumlheizung, der jährliche Energieverbrauch bei wärmerem Klimaverhältnissen	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
voor ruimteverwarming, het jaarlijkse energieverbruik onder wärmere klimaatomstandigheden	For die Raumlheizung, der jährliche Energieverbrauch bei wärmerem Klimaverhältnissen	For die Raumlheizung, der jährliche Energieverbrauch bei wärmerem Klimaverhältnissen	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias	Para calefacción espacial, el consumo anual de electricidad en condiciones climáticas medias
19	For water heating, annual energy consumption under colder climate conditions	For die Warmwasserbereitung, den jährlichen Stromverbrauch bei kaltem Klimaverhältnissen	For die Warmwasserbereitung, den jährlichen Energieverbrauch bei kaltem Klimaverhältnissen	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias
voor waterverwarming, het jaarlijkse elektriciteitsverbruik (onder koudere klimaatomstandigheden)	For waterverwarming, het jaarlijkse elektriciteitsverbruik (onder koudere klimaatomstandigheden)	For waterverwarming, het jaarlijkse elektriciteitsverbruik (onder koudere klimaatomstandigheden)	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias
20	voor waterverwarming, het jaarlijkse elektriciteitsverbruik (onder wärmere klimaatomstandigheden)	For waterverwarming, het jaarlijkse elektriciteitsverbruik (onder wärmere klimaatomstandigheden)	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias	Para calefacción de agua, el consumo anual de electricidad en condiciones climáticas medias
21	Seasonal space heating energy efficiency under colder climate conditions	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción espacial en condiciones climáticas medias
de sæsonreguleret energieffektivitet (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción espacial en condiciones climáticas medias	la eficiencia energética de calefacción espacial en condiciones climáticas medias
22	Seasonal space heating energy efficiency under warmer climate conditions	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción en condiciones climáticas medias
de sæsonreguleret energieffektivitet (under wärmere klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	de årsgennemsnitlige energiefølelighed for rumvarmning (under gennemsnitlige klimaatbetingelser)	la eficiencia energética de calefacción en condiciones climáticas medias	la eficiencia energética de calefacción en condiciones climáticas medias
23	de energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias
vedelämmityksen energiefølelisuus (keskimääräisissä ilmasto-olosuhteissa)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias	la eficiencia energética de calefacción en condiciones climáticas medias
24	de energiefølelighed for vandvarmning (under wärmere klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias
de energiefølelighed for vandvarmning (under wärmere klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	de årsgennemsnitlige energiefølelighed for vandvarmning (under gennemsnitlige klimaatomstandigheder)	la eficiencia energética de calefacción en condiciones climáticas medias	la eficiencia energética de calefacción en condiciones climáticas medias
25	Sound power level L <sub>WA, outdoor</sub>	den Schalleistungspegel L <sub>WA, im Freien</sub>	el nivel de potencia acústica L <sub>WA, en exteriores</sub>	la potencia acústica L <sub>WA, en exteriores</sub>
het geluidsemissievermogen L <sub>WA, buiten</sub>	den Schalleistungspegel L <sub>WA, im Freien</sub>	el nivel de potencia acústica L <sub>WA, en exteriores</sub>	el nivel de potencia acústica L <sub>WA, en exteriores</sub>	la potencia acústica L <sub>WA, en exteriores</sub>
hidralna akustičko ukupno L <sub>WA, van zvanjatz</sub>	hidralna akustičko ukupno L <sub>WA, van zvanjatz</sub>	el nivel de potencia acústica L <sub>WA, en exteriores</sub>	el nivel de potencia acústica L <sub>WA, en exteriores</sub>	la potencia acústica L <sub>WA, en exteriores</sub>

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**


Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	135	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	2.19	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = + 2 ° C	COPd	3.38	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	4.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	6.30	-
Tj = + 7 ° C	Pdh	4.8	kW	Tj = bivalent temperature	COPd	1.69	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	1.69	-
Tj = +12 ° C	Pdh	2.9	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	5972	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	133	%	
Daily electricity consumption	Q <sub>elec</sub>	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

Contact details  
 MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY  
 Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier:  
  
 Kenichi SAITO  
 Manager, Quality Assurance Department  
 TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.  
 · Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.  
 (\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
 (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.  
 (\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	181	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	3.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.62	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	6.00	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.96	-
Tj = + 7 ° C	Pdh	5.2	kW	Tj = bivalent temperature	COPd	2.49	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	2.49	-
Tj = +12 ° C	Pdh	3.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C	Power consumption in modes other than active mode			
Power consumption in modes other than active mode				Off mode			
Off mode	P <sub>OFF</sub>	0.022	kW	Thermostat-off mode	P <sub>TO</sub>	0.022	kW
Thermostat-off mode	P <sub>TO</sub>	0.022	kW	Standby mode	P <sub>SB</sub>	0.022	kW
Standby mode	P <sub>SB</sub>	0.022	kW	Crankcase heater mode	P <sub>CK</sub>	0.000	kW
Crankcase heater mode	P <sub>CK</sub>	0.000	kW	Other items			

Capacity control	variable		Rated air flow rate, outdoors	-	2640	m <sup>3</sup> /h
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA			
Annual energy consumption	Q <sub>HE</sub>	4480	kWh			

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	133	%	
Daily electricity consumption	Q <sub>elec</sub>	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

**Contact details**

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY

Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvari No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.

Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	116	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.1	kW	Tj = - 7 ° C	COPd	2.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	4.0	kW	Tj = + 7 ° C	COPd	4.59	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.88	-
Tj = + 7 ° C	Pdh	3.8	kW	Tj = bivalent temperature	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.59	-
Tj = +12 ° C	Pdh	4.4	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	8.0	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.0	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	8298	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	149	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.2	kW	Tj = - 7 ° C	COPd	3.71	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.35	-
Tj = + 2 ° C	Pdh	4.1	kW	Tj = + 7 ° C	COPd	5.34	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	7.50	-
Tj = + 7 ° C	Pdh	3.9	kW	Tj = bivalent temperature	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.57	-
Tj = +12 ° C	Pdh	4.5	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.96	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	7.7	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.3	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	6508	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	162	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	2.10	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	3.53	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = +12 ° C	COPd	5.75	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	2.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = operation limit temperature (***)	COPd	2.10	-
Tj = +12 ° C	Pdh	4.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.97	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	3246	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.



**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	232	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	5.55	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	7.54	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	3.50	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	3.50	-
Tj = +12 ° C	Pdh	4.4	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.96	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	2276	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

- Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.
  - Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.
- (\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
- (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.
- (\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	137	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	2.19	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = + 2 ° C	COPd	3.38	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	4.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	6.30	-
Tj = + 7 ° C	Pdh	4.8	kW	Tj = bivalent temperature	COPd	1.69	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	1.69	-
Tj = +12 ° C	Pdh	2.9	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	5891	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	133	%	
Daily electricity consumption	Q <sub>elec</sub>	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

Contact details  
 MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY  
 Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier:  
  
 Kenichi SAITO  
 Manager, Quality Assurance Department  
 TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.  
 · Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.  
 (\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
 (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.  
 (\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	185	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	3.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.62	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	6.00	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.96	-
Tj = + 7 ° C	Pdh	5.2	kW	Tj = bivalent temperature	COPd	2.49	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	2.49	-
Tj = +12 ° C	Pdh	3.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C	Other items			
Power consumption in modes other than active mode				Rated air flow rate, outdoors			
Off mode	P <sub>OFF</sub>	0.022	kW			2640	m <sup>3</sup> /h
Thermostat-off mode	P <sub>TO</sub>	0.022	kW	Capacity control	variable		
Standby mode	P <sub>SB</sub>	0.022	kW	Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA
Crankcase heater mode	P <sub>CK</sub>	0.000	kW	Annual energy consumption	Q <sub>HE</sub>	4399	kWh

For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	133	%
Daily electricity consumption	Qelec	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

**Contact details**

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY

Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvari No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.

Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	117	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.1	kW	Tj = - 7 ° C	COPd	2.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	4.0	kW	Tj = + 7 ° C	COPd	4.59	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.88	-
Tj = + 7 ° C	Pdh	3.8	kW	Tj = bivalent temperature	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.59	-
Tj = +12 ° C	Pdh	4.4	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	8.0	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.0	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	8250	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	150	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.2	kW	Tj = - 7 ° C	COPd	3.71	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.35	-
Tj = + 2 ° C	Pdh	4.1	kW	Tj = + 7 ° C	COPd	5.34	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	7.50	-
Tj = + 7 ° C	Pdh	3.9	kW	Tj = bivalent temperature	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.57	-
Tj = +12 ° C	Pdh	4.5	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.96	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	7.7	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.3	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	6459	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvari No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

- Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.
  - Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.
- (\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
- (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.
- (\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	167	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	2.10	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	3.53	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = +12 ° C	COPd	5.75	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	2.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = operation limit temperature (***)	COPd	2.10	-
Tj = +12 ° C	Pdh	4.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.97	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	3149	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	ERST30D-****D
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	242	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	5.55	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	7.54	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	3.50	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	3.50	-
Tj = +12 ° C	Pdh	4.4	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.96	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	2179	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details				MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY			
				Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey			
The identification and signature of the person empowered to bind the supplier;				Kenichi SAITO			
The signature is signed in the average climate / medium-temperature section.				Manager, Quality Assurance Department			
				TURKEY			

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**


Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	135	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	2.19	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = + 2 ° C	COPd	3.38	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	4.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	6.30	-
Tj = + 7 ° C	Pdh	4.8	kW	Tj = bivalent temperature	COPd	1.69	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	1.69	-
Tj = +12 ° C	Pdh	2.9	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	5972	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	133	%	
Daily electricity consumption	Q <sub>elec</sub>	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

Contact details  
 MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY  
 Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier:  
  
 Kenichi SAITO  
 Manager, Quality Assurance Department  
 TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.  
 · Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.  
 (\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
 (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.  
 (\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.



**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	181	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	8.9	kW	Tj = - 7 ° C	COPd	3.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.62	-
Tj = + 2 ° C	Pdh	5.4	kW	Tj = + 7 ° C	COPd	6.00	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.96	-
Tj = + 7 ° C	Pdh	5.2	kW	Tj = bivalent temperature	COPd	2.49	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	2.49	-
Tj = +12 ° C	Pdh	3.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.95	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	-10	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-10	° C	Other items			
Power consumption in modes other than active mode				Rated air flow rate, outdoors			
Off mode	P <sub>OFF</sub>	0.022	kW			2640	m <sup>3</sup> /h
Thermostat-off mode	P <sub>TO</sub>	0.022	kW	Capacity control	variable		
Standby mode	P <sub>SB</sub>	0.022	kW	Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA
Crankcase heater mode	P <sub>CK</sub>	0.000	kW	Annual energy consumption	Q <sub>HE</sub>	4480	kWh

For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	133	%
Daily electricity consumption	Q <sub>elec</sub>	6.380	kWh				
Annual electricity consumption	AEC	1404	kWh				

**Contact details**

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY

Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvari No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.

Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	116	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.1	kW	Tj = - 7 ° C	COPd	2.62	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	4.0	kW	Tj = + 7 ° C	COPd	4.59	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	6.88	-
Tj = + 7 ° C	Pdh	3.8	kW	Tj = bivalent temperature	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.59	-
Tj = +12 ° C	Pdh	4.4	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	1.57	-
Degradation co-efficient (**)	Cdh	0.97	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	8.0	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.0	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	8298	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	149	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	6.2	kW	Tj = - 7 ° C	COPd	3.71	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = + 2 ° C	COPd	4.35	-
Tj = + 2 ° C	Pdh	4.1	kW	Tj = + 7 ° C	COPd	5.34	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = +12 ° C	COPd	7.50	-
Tj = + 7 ° C	Pdh	3.9	kW	Tj = bivalent temperature	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.97	-	Tj = operation limit temperature (***)	COPd	1.57	-
Tj = +12 ° C	Pdh	4.5	kW	Tj = - 15 ° C (if TOL < - 20 ° C)	COPd	2.00	-
Degradation co-efficient (**)	Cdh	0.96	-	Operation limit temperature	TOL	-30	° C
Tj = bivalent temperature	Pdh	8.4	kW	Heating water operating limit temperature	WTOL	60	° C
Tj = operation limit temperature (***)	Pdh	7.7	kW	Supplementary heater			
Tj = - 15 ° C (if TOL < - 20 ° C)	Pdh	8.2	kW	Rated heat output (*)	Psup	2.3	kW
Bivalent temperature	Tbiv	-16	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	-22	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	6508	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	111	%	
Daily electricity consumption	Q <sub>elec</sub>	7.500	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	162	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	2.10	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	3.53	-
Degradation co-efficient (**)	Cdh	1.00	-	Tj = +12 ° C	COPd	5.75	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	2.10	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = operation limit temperature (***)	COPd	2.10	-
Tj = +12 ° C	Pdh	4.2	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.97	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	3246	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC		kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

**PRODUCT INFORMATION / TECHNICAL DOCUMENTATION**

Model(s):	Outdoor unit:	PUZ-SHWM100YAA
	Indoor unit:	EHST30D-MED
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10.0	kW	Seasonal space heating energy efficiency	$\eta_s$	232	%
Declared capacity for heating for part load at indoor temperature 20 ° C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ° C and outdoor temperature Tj			
Tj = - 7 ° C	Pdh	-	kW	Tj = - 7 ° C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj = + 2 ° C	COPd	3.50	-
Tj = + 2 ° C	Pdh	10.0	kW	Tj = + 7 ° C	COPd	5.55	-
Degradation co-efficient (**)	Cdh	0.99	-	Tj = +12 ° C	COPd	7.54	-
Tj = + 7 ° C	Pdh	6.4	kW	Tj = bivalent temperature	COPd	3.50	-
Degradation co-efficient (**)	Cdh	0.98	-	Tj = operation limit temperature (***)	COPd	3.50	-
Tj = +12 ° C	Pdh	4.4	kW	Operation limit temperature	TOL	-30	° C
Degradation co-efficient (**)	Cdh	0.96	-	Heating water operating limit temperature	WTOL	60	° C
Tj = bivalent temperature	Pdh	10.0	kW	Supplementary heater			
Tj = operation limit temperature (***)	Pdh	10.0	kW	Rated heat output (*)	Psup	0.0	kW
Bivalent temperature	Tbiv	2	° C	Type of energy input	Electrical		
Reference design conditions for space heating	Tdesignh	2	° C				
Power consumption in modes other than active mode							
Off mode	P <sub>OFF</sub>	0.022	kW				
Thermostat-off mode	P <sub>TO</sub>	0.022	kW				
Standby mode	P <sub>SB</sub>	0.022	kW				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW				

Other items				Rated air flow rate, outdoors			
Capacity control	variable			-	2640	m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	/ 58	dBA				
Annual energy consumption	Q <sub>HE</sub>	2276	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	XL			$\eta_{wh}$	155	%	
Daily electricity consumption	Q <sub>elec</sub>	5.600	kWh				
Annual electricity consumption	AEC	0	kWh				

Contact details

MITSUBISHI ELECTRIC AIR CONDITIONING SYSTEMS MANUFACTURING TURKEY JOINT STOCK COMPANY      Manisa OSB 4.Kisim Kecilikoyosb Mah. Ahmet Nazif Zorlu Bulvarı No:19 Yunusemre - Manisa, Turkey

The identification and signature of the person empowered to bind the supplier;

Kenichi SAITO

The signature is signed in the average climate / medium-temperature section.      Manager, Quality Assurance Department

TURKEY

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

(\*\*\*) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.