

PRODUCT-DETAILS

E451-5.7A

E451-5.7A Priority Switch



Informations générales

Extension du type de produit	E451-5.7A
Code de produit	2CDE16000R0901
EAN	4016779415903
Description courte	E451-5.7A Priority Switch
Description longue	Priority switches are used in installations where existing conductor cross-sections or the size of the power supply connection do not permit simultaneous operation of two powerful consumers (e.g. storage heater and heat exchanger). Priority switches disconnect the long-term consumer (storage heater) as long as the short-term consumer (heat exchanger) is switched on. The current coil of the priority switch is connected in series with the short-term consumer. When the consumer is switched on, the contact of the priority switch disconnects e.g. the contactor of the heating system.

Technique

Tension nominale (U _n)	230
Type de tension	AC
Maximum Switching Voltage	400 V
Continuous Operating Current (I _c)	43 A
Maximum Switching Power	230 W
Power Loss	2.4 W
Number of Contacts CO	0

Number of Contacts NC	1
Number of Contacts NO	0
Délai (T)	Off, Maximum, Switched Off 10 second [unit of time]
Type de montage	DIN-Rail

Environnement

Indice de protection	IP40
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CDK443005D2701
REACH Declaration	9AKK107492A1907
Informations environnementales	2CDU400022D0201
SCIP	8b7c324f-572c-4518-a6a4-50179acd3e3f Germany (DE)
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	1
Produit Largeur Net	17.5 mm
Produit Hauteur Net	85 mm
Produit Longueur Net	60 mm
Poids net	0.089 kg
Profondeur d'encastrement (t ₂)	60 mm

Commande

Emballage Niveau 1 Unités	10 pièce
Emballage Niveau 1 Poids	1.05 kg

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CDK443005D2701
--------------------------------	-----------------

Installation

Instructions et manuels	2CSC400002D0208
-------------------------	-----------------

Downloads Préférés

Fiche produit, informations techniques	9AKK106930A8017
--	-----------------

Classifications

ETIM 8	EC001655 - Load shedding relay for distribution board
ETIM 9	EC001655 - Load shedding relay for distribution board
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 49 00
eClass	V11.0 : 27142332
Code de classification d'objet	Q

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Control and Automation Devices → Dispositifs de contrôle de charge

