


Part number

# PE 1643 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V

#### Product description

<b>Product type</b>	Socket Mobile
<b>Series</b>	PE...PV, PLUSO
<b>Connection type</b>	Screw terminal connection
<b>N. of poles</b>	2 poles + 
<b>Clock position</b>	4

#### Technical data

<b>Current</b>	16 A
<b>Voltage</b>	100 ÷ 130 V
<b>IP degree of protection</b>	IP44

#### Further technical details

<b>Weight</b>	135,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 1021 yellow
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747063814
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	208,00 mm
<b>Packaging height</b>	140,00 mm
<b>Packaging width</b>	290,00 mm
<b>Sub-packaging weight</b>	1,35 kg
<b>Sub-packaging description</b>	Carton box
<b>Sub-packaging quantity</b>	10 Pcs
<b>Sub-packaging EAN barcode</b>	8015747063821


Part number

# PE 1643 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV		A	B	Ø min	Ø max
<b>16A</b>	2P+⊕	157,5	68	7	17
	3P+⊕	164,5	76	7	17
	3P+N+⊕	183,5	83	9	22
<b>32A</b>	2P+⊕	200,5	87	9	22
	3P+⊕	200,5	87	9	22
	3P+N+⊕	200,5	91	9	22

## Notes

Dimensions shown in mm are not binding and may be changed without notice.