


Part number

# PHW 6364 PV



Mobile socket outlet, PLUSO HEAVY DUTY series, 3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V

#### Product description

<b>Product type</b>	Socket Mobile
<b>Series</b>	PHW...PV, PLUSO HEAVY DUTY
<b>N. of poles</b>	3 poles + 
<b>Clock position</b>	6

#### Technical data

<b>Current</b>	63 A
<b>Voltage</b>	380 ÷ 415 V
<b>IP degree of protection</b>	IP66 / IP67

#### Further technical details

<b>Weight</b>	915,00 g
<b>Operating temperature range (min, max)</b>	-40°C ... +100°C

#### Material properties

<b>Colour</b>	RAL 7012 grey, RAL 3000 red
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747144452
-------------------	---------------

#### Packaging Information

<b>Packaging weight</b>	1,83 kg
<b>Packaging volume</b>	6,61 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	2 Pcs
<b>Packaging EAN code</b>	8015747144575


Part number

# PHW 6364 PV



## Catalogue drawings

(63 / 125A) PHW ... PV



PHW...PV		A	B	Pg ø
63A	2P+⊕	277	108,5	36
	3P+⊕	277	108,5	36
	3P+N+⊕	277	108,5	36
125A	2P+⊕	324	120,5	2"gas
	3P+⊕	324	120,5	2"gas
	3P+N+⊕	324	120,5	2"gas

## Notes

Dimensions shown in mm are not binding and may be changed without notice.

- 
- Temperature range: from -40 °C to +100 °C
  - Compliant with EN 60309-1 and -2
  - Enclosure, insert and locking ring in insulating, thermoplastic, self-extinguishing material
  - PHW...PV types (IP66/IP67), RAL 9005 black enclosure, locking ring with gasket colour coded according to the operating voltage, entry with cable gland
  - Terminals with retained screws
  - Stainless steel insert fixing screws
  - Nickel-plated contacts as standard
-