DOL-1204G05MC75KM0

Sensor/actuator cable

PLUG CONNECTORS AND CABLES



DOL-1204G05MC75KM0 | Sensor/actuator cable

PLUG CONNECTORS AND CABLES



Ordering information

Туре	Part no.
DOL-1204G05MC75KM0	2079291

Other models and accessories -> www.sick.com/Sensor_actuator_cable

Detailed technical data


Technical specifications	
Connection type head A	Female connector, M12, 4-pin, straight
Connection type head B	Flying leads
Connection type	Flying leads
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Tightening torque	0.4 Nm
Cable	5 m, 4-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Black
Cable diameter	5.9 mm
Conductor cross section	0.75 mm ²
Shielding	Unshielded
Bending radius	
Flexible use	> 10 x cable diameter
Stationary position	> 5 x cable diameter
Bending cycles	≥ 2,000,000
Defense a subbert	
Reference voltage	
Reference voltage	≤ 250 V
Current loading	≤ 250 V 4 A
Current loading	4 A
Current loading Traversing speed	4 A 3 m/s
Current loading Traversing speed Travelling distance	4 A 3 m/s 5 m
Current loading Traversing speed Travelling distance Acceleration	4 A 3 m/s 5 m $\leq 5 m/s^2$
Current loading Traversing speed Travelling distance Acceleration Signal type	4 A 3 m/s 5 m ≤ 5 m/s ² Sensor/actuator cable Zones with oils and lubricants
Current loading Traversing speed Travelling distance Acceleration Signal type Application	4 A 3 m/s 5 m ≤ 5 m/s ² Sensor/actuator cable Zones with oils and lubricants Drag chain operation
Current loading Traversing speed Travelling distance Acceleration Signal type Application Enclosure rating	4 A 3 m/s 5 m ≤ 5 m/s ² Sensor/actuator cable Zones with oils and lubricants Drag chain operation IP65/ IP67/ IP68 Head A: female connector, M12, 4-pin, straight Head B: cable Cable: for voltage supply, suit-
Current loading Traversing speed Travelling distance Acceleration Signal type Application Enclosure rating Description Operating temperature	4 A 3 m/s 5 m ≤ 5 m/s ² Sensor/actuator cable Zones with oils and lubricants Drag chain operation IP65/ IP67/ IP68 Head A: female connector, M12, 4-pin, straight Head B: cable Cable: for voltage supply, suit-

DOL-1204G05MC75KM0 | Sensor/actuator cable

PLUG CONNECTORS AND CABLES

Head	-25 °C +90 °C	
Classifications		
ECLASS 5.0	19030312	
ECLASS 5.1.4	19030312	
ECLASS 6.0	27060304	
ECLASS 6.2	27060304	
ECLASS 7.0	27060304	
ECLASS 8.0	27060304	
ECLASS 8.1	27060304	
ECLASS 9.0	27060304	
ECLASS 10.0	27060304	
ECLASS 11.0	27060304	
ECLASS 12.0	27060304	
ETIM 5.0	EC000830	
ETIM 6.0	EC000830	
ETIM 7.0	EC003249	
ETIM 8.0	EC003249	
UNSPSC 16.0901	26121604	

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

