

## Features

Use: Indoor  
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
 Emission: DIRECT  
 Optics: OPAL  
 Colour: BLACK  
 Dimming: PUSH, DALI  
 Emergency: NO  
 L: 1960mm  
 A: 53mm  
 H: 69mm  
 Made in: ITALY  
 Warranty: 5 years  
 Weight: 5kg

## Tech data

Luminaire input power: 48.3W  
 Luminaire luminous flux: 3757lm  
 IP: 40  
 Insulation class: I  
 Supply voltage: 220-240V 50/60Hz  
 SELV: Si

## Source

Light source: LED  
 Source power: 42W  
 Colour temperature: 4000K  
 CRI: >90  
 Colour tolerance: 3 Step MacAdam  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



## COMPLETION ACCESSORIES

---



HERO: MOD.CIECO 250 NE

**108676.02**

---



HERO: MOD.CIECO ANG.SX 150 NE

**108677.02**

---



HERO: MOD.CIECO ANG.DX 150 NE

**108678.02**

---



HERO: MOD.CIECO 1120 NE

**108679.02**

---



HERO: MOD.CIECO 1400 NE

**108680.02**


---



HERO: MOD.CIECO 1680 NE

**108681.02**


---



HERO: COPPIA TESTATE NE

**108684.02**

## MOUNTING ACCESSORIES



ALL-TRACK: COPPIA ADATT. 3P+DALI NER

**106723.02**



HERO: SOSPL3000 1PZ. TESTA/CODA

**108685.99**



HERO: SOSPL3000 1PZ. UNIONE

**108686.99**



HERO: STAFFA PARETE "L" NE

**108687.02**




HERO: KIT INCASSO LED (1X)

**108688.99**



HERO: SPESS. CARTONG. 10MM 2PZ.

**108689.99**




KIT ALIMENTAZIONE L1200 5P BIA

**108921.01**




KIT ALIMENTAZIONE L1200 5P NE

**108921.02**



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**



KIT ALIMENTAZIONE L3000 5P NE

**108922.02**