

Pan-Steel™ I-Series Metal Locking Ties

Mechanical fastening applications demand high quality systems that can withstand harsh environments while maintaining a safe and secure physical infrastructure. Severe weather, intense UV rays, high vibration, and galvanic corrosion are all variables that can sacrifice performance and create safety hazards. Panduit offers innovative solutions that provide reliable fastening of critical components which allows businesses to minimize risk and enhance productivity.

The Pan-Steel™ I-Series Metal Locking Ties is available in 304 and 316L stainless steel to deliver maximum performance, high strength, and enhanced job site safety, ideal for Shipbuilding, Oil and Gas, and Industrial markets. Designed to work together in extreme conditions, the I-Series metal locking ties and installation tools provide a safe and cost effective solution . This system is part of the complete range of harsh environment solutions available from Panduit.



Oil and Gas



Mining and Minerals



Shipbuilding



Pan-Steel™ I-Series Metal Locking Ties

IMLT

Type

I series = Metal Locking Tie

6

Bundle Diameter Reference (mm)

S

Cross Section

S = Standard
H = Heavy

—

C

Standard Package Size

C = 100
L = 50
Q = 25

—

Material

(blank) = 304
6L = 316 L

Pan-Steel™ Self-Locking Cable Ties – IMLT Series

- Self-locking head design speeds installation and locks into place at any length along the tie body
- Provides a strong, durable method of cable bundling
- Can be used in a wide range of indoor, outdoor, and underground (including direct burial) applications
- Smooth surfaces and rounded edges assures cable protection and worker safety
- Available in 304 stainless steel for general-purpose applications
- Available in 316L stainless steel for the most corrosive environments

Part Number	Material	Max Bundle Diameter (mm)	Min Bundle Diameter (mm)	Min Loop Tensile Strength (N)	Length (mm)	Width (mm)	Thickness (mm)	Recommended Tool	Std Pkg Qty	Std Ctn Qty
IMLT25S-C	304	25	12.7	556	127	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT51S-C	304	51	12.7	556	201	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT69S-C	304	69	12.7	556	259	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT102S-C	304	102	12.7	556	362	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT152S-C	304	152	12.7	556	521	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT203S-C	304	203	12.7	556	679	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT254S-C	304	254	12.7	556	838	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT304S-Q	304	304	12.7	556	998	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	25	125
IMLT355S-Q	304	355	12.7	556	1156	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	25	125
IMLT380S-Q	304	380	12.7	556	1250	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	25	125
IMLT25S-C6L	316L	25	12.7	556	127	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT51S-C6L	316L	51	12.7	556	201	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT69S-C6L	316L	69	12.7	556	259	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT102S-C6L	316L	102	12.7	556	362	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT152S-C6L	316L	152	12.7	556	521	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT203S-C6L	316L	203	12.7	556	679	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT254S-C6L	316L	254	12.7	556	838	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT304S-C6L	316L	304	12.7	556	998	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT355S-C6L	316L	355	12.7	556	1156	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT380S-C6L	316L	380	12.7	556	1250	4.6	0.25	GS4MT, HTMT, PPTMT, ST2MT	100	500
IMLT51H-L	304	51	12.7	890	201	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT69H-L	304	69	12.7	890	259	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT102H-L	304	102	12.7	890	362	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT152H-L	304	152	12.7	890	521	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT203H-L	304	203	12.7	890	679	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT254H-L	304	254	12.7	890	838	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT304H-L	304	304	12.7	890	998	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT355H-L	304	355	12.7	890	1156	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT51H-L6L	316L	51	12.7	890	201	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT69H-L6L	316L	69	12.7	890	259	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT102H-L6L	316L	102	12.7	890	362	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT152H-L6L	316L	152	12.7	890	521	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT203H-L6L	316L	203	12.7	890	679	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT254H-L6L	316L	254	12.7	890	838	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT304H-L6L	316L	304	12.7	890	998	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250
IMLT355H-L6L	316L	355	12.7	890	1156	7.9	0.25	GS4MT, HTMT, PPTMT, ST2MT, PBTMT	50	250

*Other lengths available, contact Panduit Customer Service.

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT™

©2015 Panduit Corp.
ALL RIGHTS RESERVED.
SSCB31--WW-JPN
2/2016