



Maxos, Accessoires

9MX056 EC7

ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Données du produit

Informations générales	
Couleur des accessoires	-
Code famille de produits	9MX056 [ACC MAXOS]
Fonctionnement et électricité	
Fréquence linéaire	50 to 60 Hz
Tension d'entrée	220 à 240 V
Approbation et application	
Indice de protection	-
Classe de protection CEI	Classe de sécurité I

Données du produit	
Code EOC	403073213179200
Nom du produit de la commande	9MX056 EC7
Code de commande	13179200
Quantité par pack	1
Conditionnement par carton	1
Code 12NC	910605019226
Nom de produit complet	9MX056 EC7
Codes EAN/UPC - Boîte	4030732131792