

PRODUCT-DETAILS

## 20 MUCB2USB-83-500

### Socket Earthing pin with USB AA aluminium silver - 63x63



#### Informations générales

Extension du type de produit	20 MUCB2USB-83-500
Code de produit	2CKA002017A1890
EAN	4011395303993
Description courte	Socket Earthing pin with USB AA aluminium silver - 63x63
Description longue	For connecting electric loads. DP (2 P + E) With screwless terminals. For supply and support of mobile devices via USB-cable. With two USB type A outputs. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. Support of loading protocol on the USB-A connection: Apple MFI with 2.4 A and BC 1.2 with 1.5 A. With electronic short-circuit protection. With electronic overload protection. Suitable for the countries: Belgium, Poland, Czech Republic.

#### Installation

Instructions et manuels	No document needed
-------------------------	--------------------

#### Technique

Fiche produit, informations techniques	No document needed
Fonction	USB

Tension nominale (U <sub>r</sub> )	230 V
Secondary Voltage	5 V
Courant nominal (I <sub>n</sub> )	16 A
Fréquence (f)	50 ... 60 Hz
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	0.075 W
Nombre de phases	1
Nombre de sorties	2
Number of Gangs	1
Design Range	63x63 future linear Busch-axcent Busch-axcent pur
Type de raccordement	Plug Clamp
Type de charge	Earth pin socket
Type de montage	Flush Mounted
Socket Outlet Type	Earthing Pin
Type of Fastening	Mounting with Claw Mounting with Screw
Finition de surface	Lacquered Matt
Matériau	Thermoplastic
Label Space Provided	No
Pictogramme	None
Model Number	Earthing pin
RAL Number	RAL 9006 - Aluminium blanc
Couleur	aluminium silver
Poids de la batterie	0 g
Application Function	Mobile Device Charging Hospitality

## Environnement

Température de l'air ambiant	Operation 5 ... +35 °C
Indice de protection	IP20
Statut RoHS	No declaration needed
Informations RoHS	2CKA200000E7259
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Technique UL/CSA

Short-Circuit Current Rating (SCCR)	0 kA
-------------------------------------	------

---

## Dimensions

Produit Largeur Net	71 mm
Produit Hauteur Net	71 mm
Produit Longueur Net	57 mm
Poids net	191 g
Profondeur d'encastrement (t <sub>2</sub> )	39.5 mm

---

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E4445
--------------------------------	-----------------

---

## Classifications

ETIM 8	EC000125 - Socket outlet
ETIM 9	EC000125 - Socket outlet
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
CN8	8536 69 90
eClass	V11.0 : 27144042

---

## Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

