

PRODUCT-DETAILS

# OT630KFCC4BA

## OT630KFCC4BA Encl. Switch Disconnecter



### Informations générales

Extension du type de produit	OT630KFCC4BA
Code de produit	1SCA022834R1000
EAN	6417019289465
Description courte	OT630KFCC4BA Encl. Switch Disconnecter
Description longue	Encl. Switch Disconnecter, 4-p. 415V AC23 570A, 315kW. Plastic enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included.

### Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
Informations RoHS	1SCC340075D0201
Toxic Substances Control Act - TSCA	1SCC340095D0201

### Commande

Quantité minimum	1 pièce
Code douanier	85363090
Pays d'origine	Finland (FI)

## Downloads Préférés

Fiche produit, informations techniques	1SCC340015C0201
Instructions et manuels	1SCC340015M0004
Mechanical Drawings	OTPK765625P2II.stp

## Dimensions

Produit Largeur Net	560 mm
Produit Hauteur Net	760 mm
Produit Longueur Net	250 mm
Poids net	17.83 kg

## Technique

Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 570 A (690 V) 570 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 570 A (500 V) 570 A (690 V) 570 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 315 kW (500 V) 400 kW (690 V) 560 kW
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 570 A
Tension assignée d'isolement ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Tension	Circuit principal 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1000 V AC) 80 kA
Courant assigné de courte durée admissible ( $I_{cw}$ )	for 1 s 20 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	90 kA
Power Loss	at Rated Operating Conditions per Pole 25 W
Degré de pollution	3
Handle Color	Red / Yellow
Handle Type	Pistol handle
Normes et standards	IEC 60947-1, -3
Nombre de pôles	4
Neutral Type	Switchable neutral
Connecting Capacity Main Circuit	Hole Diameter 12 mm Screw Clamp / PE Terminal 4pc,25 ... 120 mm <sup>2</sup>
Cable Entry Position	Top/Bottom
Cable Outlets Per Side	2xII-flange / 2xII-flange
Indice de protection	acc. to IEC 60529 IP65
Résistance aux chocs	Housing IK08
Matériau du boîtier	Plastic
Maximum Mounted	2 NO, 2 NC

**Auxiliary Contacts**

Mounted Auxiliary Contacts	0 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Couple de serrage	Main Circuit 75 N·m

**Technique UL/CSA**

Couple de serrage	Main Circuit 75 N·m
-------------------	---------------------

**Environnement**

Statut RoHS	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

**Certificats et Déclarations (Numéro de document)**

Déclaration de Conformité - CE	1SCC340029D2704
REACH Declaration	1SCC340076D0201

**Emballage**

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	575 mm
Emballage Niveau 1 Longueur	780 mm
Emballage Niveau 1 Hauteur	340 mm
Emballage Niveau 1 Poids	20 kg
Emballage Niveau 1 EAN	6417019289465

**Classifications**

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
Catégorie DEEE	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Catégories

---

Produits basse tension → Interrupteurs et appareillage à fusibles en coffret → Interrupteurs-sectionneurs en coffret → Enclosed Switch-Disconnectors

