



NOTES:

READ PRODUCT INSTRUCTIONS BEFORE USING

1. Attach unit to isolation module using four (4) #4 self-tapping screws (included). Use #4 OR #6 screws for mounting to panel (not incl.)
2. Mating connector is provided

ENVIRONMENT

Operating Temperature: -25°C to 60°C (-13°F to +140°F)
 Storage Temperature: -45°C to 85°C (-49°F to 185°F)
 Humidity: 5 to 90% non-condensing: Rated 80% at 40°C, decreasing linearly to 50% at 60°C

Pollution Degree: 3
 Degree of Protection: IP20
 Altitude: Up to 5000 meters (3.2 miles)

Power*

Power over Ethernet: PoE (10/100)
 IEEE 802.at (-af) Type 1 Class III PoE topology
 DC Input: 12-24 VDC
 24-14 AWG (0.75 - 1.5mm²) Solid/Stranded
 Current Draw: 43 mA @ 24V (AVT + Network Module)
 Power Consumption: 1.1W (AVT + Network Module)
 *Note: Network Module supplies power to the AVT.
 No additional AVT power required (battery or DC)

Weight: .4 lbs (.18kg)

VERISAFE NETWORK MODULE

UNIT MOUNTING LOCATIONS MARKED 'A' (SEE NOTE 1)

						TITLE VERISAFE 2.0 NETWORK MODULE	
						CUSTOMER DRAWING	
						ITEM REVISION NAME 18I216AW/00	PANDUIT
						DATASET FILE NAME 18I216AW_DC/00	
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]	
						.x ± .06 [1.50]	.xxx ± .01 [.25]
						.xx ± .02 [.50]	ANGLES ± 5°
0	4/8/22	DFA	ZSG	MSAD	INITIAL RELEASE	GAEEN06495	MATERIAL: N/A
						DRAWING NUMBER: 18I216AW_DC	
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY DFA
							DATE 4/8/22
							CHK MSAD
							SCALE NONE
							SHT 1 OF 1
							SIZE B