

## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: SPOT  
Beam: 34°  
Colour: WHITE  
Dimming: PUSH, DALI  
Emergency: NO  
L: 1120mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 3.4kg

## Tech data

Luminaire input power: 29W  
Luminaire luminous flux: 2230lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 2X13W  
Source luminous flux: 2750lm  
Colour temperature: 3000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



## COMPLETION ACCESSORIES

---



HERO: MOD.CIECO 250 BIA

108676.01


---



HERO: MOD.CIECO ANG.SX 150 BIA

108677.01


---



HERO: MOD.CIECO ANG.DX 150 BIA

108678.01


---



HERO: MOD.CIECO 1120 BIA

108679.01


---



HERO: MOD.CIECO 1400 BIA

108680.01


---



HERO: MOD.CIECO 1680 BIA

108681.01


---



HERO: COPPIA TESTATE BIA

108684.01

## MOUNTING ACCESSORIES



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

106723.01



HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99



HERO: STAFFA PARETE "L" BIA

108687.01



HERO: KIT INCASSO LED (1X)

108688.99




HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 5P BIA

**108921.01**



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**