

PRODUCT-DETAILS

E217-16-10C220

E217-16-10C220 Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 0NC, 0CO, EI.
Color: Grey, 1LED, Red, MW: 0.5



Informations générales

Extension du type de produit	E217-16-10C220
Code de produit	2CCA703166R0001
EAN	7612270939145
Description courte	E217-16-10C220 Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 0NC, 0CO, EI. Color: Grey, 1LED, Red, MW: 0.5
Description longue	Pushbutton 1 NO / 1 NC with maintenance-free LED, Rated current: 16A/250 VACPDC, LED colour: red, 115-250 VACPDC, 12-48 VACDCPDC, 110-220 VDCPDC, Module width 0,5

Technique

Normes et standards	EN60068-2-1 EN60068-2-2 EN60068-2-30 DIN EN 60669-1 VDE 0632-1 UL508
Tension nominale (U _r)	Lamp 230 ... 250 V
Tension	acc. to EN 250 V AC acc. to UL 508 240 V AC
Voltage Range	60 ... 220 V DC
Auxiliary Voltage AC/DC	LED Indicator 60...220 V AC
Maximum Switching Voltage	250 V
Courant nominal (I _n)	16 A

Fréquence assignée (f)	50/60 Hz
Power Loss	1.5 W
Puissance Watt	1.1 W
Number of Contacts CO	0
Number of Contacts NC	0
Number of Contacts NO	1
Number of Main Contacts NC	0
Number of Main Contacts NO	1
Number of Auxiliary Contacts CO (SPDT)	0
Nombre de pôles	1
Nombre de LED	1
Couple de serrage	1.2-1.5 N·m
Switch Type	Double Interrupting Contacts
Material of Conductor	Copper
Options Provided	1 NO
Remarques	Sealable in the On and Off positions
Couleur	Red
Control Element Color	Grey
Lamp Color	Red
Connecting Capacity	Solid 1x1...6 mm ² Solid 2x2.5 mm ² Flexible 1x0.75...2x2.5 mm ²

Environnement

Température de l'air ambiant	Operation -25...+55 °C Storage -40...+70 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CCC441014D0201
REACH Declaration	2CCC005047D0201
Informations environnementales	2CCC441003C0201
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	0.5
Produit Largeur Net	9 mm
Produit Hauteur Net	85 mm
Produit Longueur Net	68 mm
Poids net	53 g
Profondeur d'encastrement (t ₂)	68 mm

Commande

Emballage Niveau 1 Unités	box 10 pièce
---------------------------	--------------

Emballage Niveau 1 Poids	594 g
E-Number (Finland)	2312334
E-Number (Switzerland)	467572148

Certificats et Déclarations (Numéro de document)

CB Certificate	9AKK108466A3845
CCC Certificate	9AKK108466A3829
Déclaration de Conformité - CE	2CCC441014D0201
Declaration of Conformity - UKCA	9AKK108467A6137
EAC Certificate	9AKK107991A4779
VDE Certificate	9AKK107991A9822

Installation

Instructions et manuels	No document needed
-------------------------	--------------------

Downloads Préférés

Fiche produit, informations techniques	2CCC441003C0101
--	-----------------

Classifications

ETIM 8	EC001546 - Push button for distribution board
ETIM 9	EC001546 - Push button for distribution board
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365053
eClass	V11.0 : 27142302
Code de classification d'objet	S

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

