## Part number QM V P4





Empty board for construction sites, Q series, for 4 PE/PEW...PQ/PQF sockets, for flange 80x80 mm

Product description		Material properties		
Product type	Empty board for construction sites		Complia	
Series	Q	RoHs conformity	6(c): co weight	
Specification	For 4 PE/PEWPQ/PQF sockets For flange 80x80 mm	China RoHs - EFUP	50	
Technical data		REACH SVHC substances	Yes Lead	
IP degree of protection	IP55	SCIP number	8567b5	
Further technical details				
Weight	4.580.00 g	General ordering information		
		EAN13 code	801574	
Operating temperature range (min, max)	-40°C +125°C	Packaging Information		
<b>3 3 1 1</b>		Packaging weight	4,58 kg	
		Packaging volume	55,44 d	

Material properties		
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight	
China RoHs - EFUP	50	
<b>REACH SVHC</b> substances	Yes Lead	
SCIP number	8567b55c-b9a9-4eac-a85e-95b20aab14a0	
General ordering informati	on	
EAN13 code	8015747164047	
Packaging Information		
Packaging weight	4,58 kg	
Packaging volume	55,44 dm³	
Packaging description	Carton box	
Packaging quantity	1 Pcs	
Packaging EAN code	8015747164320	

## Part number QM V P4



## Catalogue drawings

	QM V P6 site board		QM V P4 site board	s
	assembly kit	T	assembly kit	
description	Part No.		Part No.	
empty board to be assembled: 6 openings for PE / PEWPQ / PQF socket-outlets with 80x80mm flange	QM V P6			
empty board to be assembled: - 4 openings for PE / PEWPQ / PQF socket-outlets with 80x80mm flange			QM V P4	
comprising: 1 rail half shell complete with spring hinged cover 1 socket-outlet half shell 1 DIN EN 60715, 219 mm rail with fastening screws 1 Pg 21 IP65 angled cable gland 1 25 mm <sup>3</sup> earth terminal 1 6 set[ faoping stainless steel screws, suitable for	dimensions in mm QM V P6	毘		
1 20 mini edui returniari 16 sell'tapping stainless steel screws, suitable for plastics, 3.9x19 mm (QM V P4), mixed cuts / Ph (to fasten socket-outlets) - 24 self tapping stainless steel screws, suitable for plastics, 3.9x19 mm (QM V P6), mixed cuts / Ph (to fasten socket-outlets)		0 0	442	
<ol> <li>cable clamp + 2 screws, 3.9x32 mm + 2 fall washers Ø 48 mm to fix the cable clamp - 6 self tapping screws, 3.9x22 mm with stainless steel fat washers (6 to khaf århelis)</li> <li>2 DIN module blanking units</li> <li>1 plate to be filled with data</li> <li>1 document holder pocket</li> </ol>		270	382	
	QM V P4			( • ////¢//// • )
			442	
	- 270	270		
dimensions are not binding and may be changed without prior notice				
The second price in COURSE				

## Notes

Dimensions shown in mm are not binding and may be changed without notice.