

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Dimming: ON/OFF
Emergency: NO
L: 1200mm
A: 1200mm
H: 90mm
D: 1225mm
Made in: ITALY
Warranty: 5 years
Weight: 18.4kg

Tech data

Luminaire input power: 119.4W
Luminaire luminous flux: 15911lm
IP: 20
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 108W
Source luminous flux: 19416lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

MOUNTING ACCESSORIES



ROTO: ALIMENTAZIONE L1200 3P. BIA

104423.01



ROTO: ALIMENTAZIONE L3000 3P. BIA.

104425.01



ROTO: D=1200 KIT 4 SOSP. L3000

104429.99