

PRODUCT-DETAILS

20 MUCB2USB-81-500

Socket Outlets with USB AA anthracite - 63x63



Informations générales

Extension du type de produit	20 MUCB2USB-81-500
Code de produit	2CKA002011A6290
EAN	4011395303979
Description courte	Socket Outlets with USB AA anthracite - 63x63
Description longue	For connecting electric loads. DP (2 P + E) With screwless terminals. For supply and support of mobile devices via USB-cable. With two USB type A outputs. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. Support of loading protocol on the USB-A connection: Apple MFI with 2.4 A and BC 1.2 with 1.5 A. With electronic short-circuit protection. With electronic overload protection. Suitable for the countries: Belgium, Poland, Czech Republic.

Technique

Fonction	USB
Tension nominale (U_r)	230 V
Secondary Voltage	5 V
Courant nominal (I_n)	16 A
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	0.075 W
Nombre de sorties	2

Design Range	63x63 future linear Busch-axcent Busch-axcent pur Busch-Dynasty carat
Type de charge	Earth pin socket
Type de montage	Flush Mounted
Socket Outlet Type	Earthing Pin
Type of Fastening	Mounting with Claw Mounting with Screw
Couleur	anthracite
Poids de la batterie	0 g
Application Function	Hospitality Mobile Device Charging

Environnement

Température de l'air ambiant	Operation 5 ... +35 °C
Indice de protection	IP20
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Profondeur d'encastrement (t ₂)	39.5 mm
---	---------

Classifications

ETIM 8	EC000125 - Socket outlet
ETIM 9	EC000125 - Socket outlet
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
CN8	8536 69 90
eClass	V11.0 : 27144042

Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

