

SMART[PRO]e 4M is a high power LED floodlight for outdoor and indoor use, ideal for illuminating medium-sized areas and sports facilities. It can be installed on walls, ceilings or the ground thanks to its galvanised steel bracket, painted with polyester powder with trivalent passivation and equipped with an adjustable goniometric scale.

EN AB 46100 die-cast aluminium housing with integrated passive heat sink and polyester powder-coated frame with trivalent passivation. COB LED technology for high efficacy.


Reflector made of metallised PC HT or anodised and polished aluminium. 4mm thick toughened front glass, silkscreen printed for symmetrical versions or with anti-reflective nanocoating for asymmetrical versions. Anti-ageing silicone gaskets and A2 stainless steel external screws. Plastic venting and anti-condensation device. Electrical connection via H07RN-F cable. Insulation Class 1.

Power supply unit and IP68 connector kit supplied separately. Available with five different types of optics, three types of Correlated Colour Temperature (3000K / 4000K / 5700K) and two different types of Colour Rendering Index (CRI>70, CRI>80).


Designed to withstand overvoltage up to 6KV (differential mode) and 10KV (common mode), temperature variations from -30°C to +50°C, water and dust penetration up to IP66, and impact up to IK08.

GENERAL INFORMATION		OPTIC AND ILLUMINATING FEATURES	
Context	Proiezione e impianti sportivi di piccole e medie dimensioni	Optic	SW - Symmetrical Wide
Luminaire	Apparecchio per proiezione LED di alta potenza	Unified Glare Rating	G*6 - ULOR = 0%
Application	Indoor / Outdoor	Lumen output (lm)	90000
Unique digital code (Datamatrix)	Currently not present	Efficiency (lm/W)	150
Colour	Graphite grey	Colour temperature	4000 K
Type of light source	LED	Color Rendering Index	CRI>70
System power	600 W	Standard Deviation Colour Matching	SDCM = 3
LED Lifetime	L90B10 (Tq+25°C) = 100000h; L80B10 (Tq+25°C) > 150000h	Photobiological Risk Class	RG1
Weight (kg)	15	Standard	EN60598-1; EN60598-2-5; IEC62778; EN13201
Warranty	5 years	ELETRICAL AND LIGHTING FEATURES	
Stocking temperature	-	Supply voltage	See external supply unit
Operating temperature	-30 +50 °C	Rated frequency (Hz)	See external supply unit
MATERIALS		Driver	Included
Body	Die-cast aluminium	Driver failure rate	See external supply unit
Shield type	Flat tempered glass 4mm	Overvoltage protection	See external supply unit
Optic	Riflettore in PC HT metallizzato	Control System	See external supply unit
Gasket	Anti-ageing silicone	INSTALLATION AND MAINTENANCE	
Locking Hook	-	Mounting and installation	High-mast lighting - Wall mounting - Ground mouting
External screw	Stainless steel	Tilt	Rotation on bracket with integrated goniometer
Colour	Verniciato a polvere poliestere con fondo epossidico	Wiring	Connettore stagno tra proiettore e gruppo di alimentazione - da ordinare separatamente
STANDARDS AND APPROVALS		Fixing	Bracket
Classification	-	Light souce replaceability	By professional
Device with reduced surface temperature	-	Controlgear replaceability	-
DIN 18032-3 certification	Yes	Driver Box	External
IPEA	-	Maximum surface exposed to the wind	0,222 m2
Insulation class	I	-	-
IP degree	IP66	-	-
Mechanical resistance	IK08	-	-
-	-	-	-

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



Smart [PRO]e

TECHNICAL SYMBOLOGY



IP
IP66

IK
IK08

STANDARDS/APPROVALS

