


Product designation	Spring return actuator without cap
Product type designation	LPSXB3
<b>General characteristics</b>	

Material	Aluminium and zinc alloy for metal parts and polyamide for plastic parts
----------	--

<b>Ambient conditions</b>									
Temperature									
Operating temperature	<table border="0" style="width: 100%;"> <tr> <td style="width: 10%;"></td> <td style="width: 10%; text-align: right;">min</td> <td style="width: 10%; text-align: right;">°C</td> <td style="width: 10%; text-align: right;">-25</td> </tr> <tr> <td></td> <td style="text-align: right;">max</td> <td style="text-align: right;">°C</td> <td style="text-align: right;">+70</td> </tr> </table>		min	°C	-25		max	°C	+70
	min	°C	-25						
	max	°C	+70						
Storage temperature	<table border="0" style="width: 100%;"> <tr> <td style="width: 10%;"></td> <td style="width: 10%; text-align: right;">min</td> <td style="width: 10%; text-align: right;">°C</td> <td style="width: 10%; text-align: right;">-40</td> </tr> <tr> <td></td> <td style="text-align: right;">max</td> <td style="text-align: right;">°C</td> <td style="text-align: right;">+85</td> </tr> </table>		min	°C	-40		max	°C	+85
	min	°C	-40						
	max	°C	+85						

<b>Dimensions</b>
-------------------



<b>Certifications and compliance</b>	
Compliance	/
Certificates	/

<b>ETIM classification</b>	
ETIM 8.0	EC002498 - Accessories/spare parts for low-voltage switch technology