

# TRIFLOW

---

## Technical Data Sheet

---

Product name: Triflow	Creation date: /2017	Version: 1.0
		Replaces: 0.0

---

### Section 1 : General description

General light lubricant. Based on mineral oils and PTFE.

### Section 2 : Features

- High penetration capability to loosen rusted and jammed parts
- Displaces moisture
- Protects against future corrosion and moisture deposit.
- The high hydrocarbon content allows efficient cleaning.
- The oil with PTFE added, performs as an adequate lubricant.

### Section 3: Applications

General light lubrication and temporarily corrosion protection.

Machines and machine parts:

- When used as a cleaner, a remnant of protective oil covers the metal surfaces during temporarily storage.
- Small articulation points take advantage of the lubrication quality.
- Guidings and slide surfaces get protection and good sliding capacity when covered with a film of the Triflow.

### Section 4: Directions

Never mix with other lubricants.

Apply a thin film over the area to treat.

To obtain protection after treatment, do not wipe of.

***A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.***



## Section 5: Typical product data (without propellant)

Aspect	:	liquid
Color	:	amber
Recommended film thickness	:	2 $\mu\text{m}$
Density at 20°C	:	1 g/cm <sup>3</sup>
Operational temperature	:	-52°C to +247°C
Salt spray resistance	:	100 h
Falex	:	3700 lbs
Coefficient of friction	:	0.08
Transversal resistivity	:	$\geq 1.10^{14} \text{ } \Omega \cdot \text{cm}$

## Section 6: Packaging

Aerosol      12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.