

PRODUCT-DETAILS

CM-SRS.22S

CM-SRS.22S Current monitoring relay 2c/o, B-C=0.3-15A RMS, 110-130VAC



Informations générales

Extension du type de produit	CM-SRS.22S
Code de produit	1SVR730841R0500
EAN	4016779852319
Description courte	CM-SRS.22S Current monitoring relay 2c/o, B-C=0.3-15A RMS, 110-130VAC
Description longue	<p>The CM-SRS.22S is a single-functional current monitoring relay from the CM single-phase monitors range. This monitoring relay operates with a rated control supply voltage of 110 - 130 V AC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It provides a RMS measuring principle for DC and AC currents with 3 measuring ranges: 0.3-1.5 A, 1-5 A and 3-15 A and works according to the open-circuit principle. The CM-SRS.22S is configurable for over- or undercurrent monitoring. The hysteresis is adjustable within a range of 3 to 30 % of the threshold value and the tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.</p>

Commande

EAN	4016779852319
Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Fiche produit, informations	2CDC112168D0201
-----------------------------	-----------------

techniques

Instructions et manuels	1SVC730720M1000 1SVC730720M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	22.5 mm
Produit Hauteur Net	85.6 mm
Produit Longueur Net	103.7 mm
Poids net	0.181 kg

Technique

Fonction	Over- or undercurrent monitoring
Plage de mesure	0.3 ... 1.5 A 1 ... 5 A 3 ... 15 A
Time Range	0 s or 0.1 ... 30 s tripping delay (ON)
Rated Control Supply Voltage (U_s)	110 ... 130 V AC
Sortie	2 c/o (SPDT) contacts
Type de borne	Screw Terminals
Rated Operational Current AC-12 (I_{θ})	(230 V) 4 A
Courant assignée d'emploi AC-15 (I_{θ})	(230 V) 3 A
Rated Operational Current DC-12 (I_{θ})	(24 V) 4 A
Courant assignée d'emploi DC-13 (I_{θ})	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Tension assignée de tenue aux chocs (U_{imp})	Measuring Circuit / Output Circuit 6 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 4 kV
Tension assignée d'isolement (U_i)	Measuring Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 250 V Supply Circuit / Measuring Circuit 600 V Supply Circuit / Output Circuit 250 V
Indice de protection	Housing IP50 Terminals IP20
Catégorie de Surtension	III
Degré de pollution	3
Dispositif de protection contre les courts-circuits	Output Circuit NC - F Type Fuses 10 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Durabilite mecanique	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Couple de serrage	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm

Recommended Screw Driver	0.8 x 4 4.5 Pozidriv 1
Type d'encastrement	1 ... 6
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Normes et standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in-lb
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environnement

Température de l'air ambiant	Operation -20 ... +60 °C Storage -40 ... +85 °C
Altitude de fonctionnement maximale autorisée	Without Derating 2000 m
REACH Declaration	1SVD981001-4501
Informations RoHS	1SVD981013-00
Statut RoHS	Following EU Directive 2011/65/EU

Valeur Circulaire

Instructions relatives à la fin de vie	1SAC200290H0001
--	-----------------

Certificats et Déclarations (Numéro de document)

CB Certificate	CB_DK-28255-UL
CQC Certificate	CQC2007010303243843
Certificat ecULus	cULus508_20120203-E140448
Declaration of Conformity - CCC	2020980303000196
Déclaration de Conformité - CE	1SVD981013-00
Declaration of Conformity - UKCA	1SVD981013-10
DNV GL Certificate	DVN_GL_TAA0000293
EAC Certificate	EAC_RU_C-DE.ME77.B.03424

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	97 mm
Emballage Niveau 1 Longueur	30 mm
Emballage Niveau 1 Hauteur	109 mm
Emballage Niveau 1 Poids	0.203 kg
Emballage Niveau 1 EAN	4016779852319

Classifications

Code de classification d'objet	B
ETIM 7	EC001440 - Current monitoring relay
ETIM 8	EC001440 - Current monitoring relay
ETIM 9	EC001440 - Current monitoring relay
eClass	V11.0 : 27371802
UNSPSC	39122332
E-Number (Finland)	2712316
E-Number (Sweden)	3860634

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Contrôle de réseau monophasé

