

PRODUCT-DETAILS

6819/59-183-500

Presence Detector 24 m DALI



Informations générales

Extension du type de produit	6819/59-183-500
Code de produit	2CKA006800A2795
EAN	4011395218266
Description courte	Presence Detector 24 m DALI
Description longue	DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 24 m x 3 m, frontal/lengthways to the detector 14 m x 3 m. Mounting height 27 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 92 sectors with 368 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Technique

Fiche produit, informations techniques	2CKA001673B9577
Fonction	Extension unit
Adapté pour	2CKA006800A2783 2CKA006800A2801 2CKA006899A2304
Tension nominale (U _r)	230 V AC
Auxiliary Voltage AC/DC	9.5 V 22.5 V AC/DC

Type de tension	DC
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50 / 60 Hz
Power Loss	0.3 W
Plage de mesure	24 m
Number of Switching Zones	368
Compatible Bus Systems	DALI
Minimum Switching Time	Switch-On 60 second [unit of time]
Type de raccordement	Plug Clamp
Type de montage	Built-in
Sensor Type	Passive infrared
Finition de surface	Surface protection: Lacquered Surface finishing: Matt
Matériau	Thermoplastic
Type d'encastrement	Ceiling
Flux lumineux	5 ... 2000 lx
Model Number	Presence detector
RAL Number	RAL 9006 - Aluminium blanc
Couleur	aluminium silver
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP40
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6536
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	94 mm
Produit Hauteur Net	94 mm
Produit Longueur Net	76 mm
Poids net	152.2 g
Profondeur d'encastrement (t ₂)	49 mm

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA200000E6536
--------------------------------	-----------------

Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete

Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2783	Presence Detector 30 m DALI 1380 W	6819/55-183-500	1	piece
2CKA006800A2801	Presence Detector	6889/50-24-500	1	piece
2CKA006899A2304	Protection Cover	6898	1	piece

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

