

Features

Use: Indoor
 Type of installation: SUSPENDED
 Emission: DIRECT/INDIRECT
 Optics: OPAL
 Colour: WHITE
 Dimming: PUSH, DALI
 Emergency: NO
 L: 1200mm
 A: 1200mm
 H: 90mm
 Made in: ITALY
 Warranty: 5 years
 Weight: 28kg

Tech data

Luminaire input power: 213.4W
 Luminaire luminous flux: 23422lm
 Direct luminous flux: 16388lm
 Indirect luminous flux: 7034lm
 IP: 40
 Insulation class: I
 Supply voltage: 220-240V 50/60Hz
 SELV: No

Source

Light source: LED
 Source power: 192W
 Source luminous flux: 32106lm
 Colour temperature: 4000K
 CRI: >80
 Colour tolerance: 3 Step MacAdam
 LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

MOUNTING ACCESSORIES



ROTO: ALIMENTAZIONE L1200 5P. BIA.

104424.01



ROTO: ALIMENTAZIONE L3000 5P. BIA.

104426.01



ROTO: D=1200 KIT 4 SOSP. L3000

104429.99
