

Features

Use: Indoor
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
 Emission: DIRECT
 Optics: OPAL
 Colour: BLACK
 Dimming: PUSH, DALI
 Emergency: NO
 L: 2240mm
 A: 53mm
 H: 69mm
 Made in: ITALY
 Warranty: 5 years
 Weight: 5.6kg

Tech data

Luminaire input power: 57.6W
 Luminaire luminous flux: 4294lm
 IP: 40
 Insulation class: I
 Supply voltage: 220-240V 50/60Hz
 SELV: Si

Source

Light source: LED
 Source power: 48W
 Colour temperature: 4000K
 CRI: >90
 Colour tolerance: 3 Step MacAdam
 LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



COMPLETION ACCESSORIES



HERO: MOD.CIECO 250 NE

108676.02



HERO: MOD.CIECO ANG.SX 150 NE

108677.02



HERO: MOD.CIECO ANG.DX 150 NE

108678.02



HERO: MOD.CIECO 1120 NE

108679.02




HERO: MOD.CIECO 1400 NE

108680.02



HERO: MOD.CIECO 1680 NE


108681.02



HERO: COPPIA TESTATE NE

108684.02

MOUNTING ACCESSORIES



ALL-TRACK: COPPIA ADATT. 3P+DALI NER

106723.02



HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99



HERO: STAFFA PARETE "L" NE

108687.02



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



KIT ALIMENTAZIONE L1200 5P NE

108921.02



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



KIT ALIMENTAZIONE L3000 5P NE

108922.02