1SNK710020R0000 ACTIVE



ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK710020R0000

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block,

Blue, Product Spacing .394 in [10 mm], 2 Position, DIN Rail,

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks









PI-Spring Terminal Block



Block Function: Feed-Through

Modular Terminal Block Product Type: PI-Spring Terminal Block

Rated Cross Section: 10 mm² Primary Product Color: Blue

Modular Terminal Block Product Type

Features

Product Type Features

Configuration Features	
Gauge Type	A6 & 5.1 mm Dia.
Number of Levels	1
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (CSA)	55 A
Power Loss	1 W
Short-Time Withstanding Current Rating @ 1s	1200 A
Voltage Rating (IEC)	1000 V
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Voltage Rating (CSA)	600 V



Dielectric Test Voltage Current Rating (UL) 55 A Current Rating (IEC) 57 A Body Features Product Weight 27.2 g[1.071 oz] Primary Product Color Blue Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp Main Circuit Capacity - Twin Ferrule per Spring Clamp 55 - 4 mm²
Current Rating (IEC) 57 A Body Features Product Weight 27.2 g[1.071 oz] Primary Product Color Blue Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp .5 – 16 mm²
Body Features Product Weight 27.2 g[1.071 oz] Primary Product Color Blue Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp ST. 2 g[1.071 oz] Blue
Product Weight 27.2 g[1.071 oz] Primary Product Color Blue Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp .5 – 16 mm²
Primary Product Color Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp .5 – 16 mm²
Mechanical Attachment DIN Rail Mounting Type TH35-15, TH35-7.5 Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp .5 – 16 mm²
DIN Rail Mounting Type Connector Mounting Type DIN Rail Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp .5 – 16 mm²
Connector Mounting Type Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp
Housing Features Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring .5 – 16 mm² Clamp
Housing Material Polyamide Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp Clamp
Dimensions Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring .5 – 16 mm² Clamp
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring .5 – 16 mm² Clamp
Clamp
Main Circuit Capacity - Twin Ferrule per Spring Clamp .5 – 4 mm²
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp .5 – 10 mm²
Wire Stripping Length 15 mm[.591 in]
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp .5 – 10 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp 20 – 8 AWG
Tool Size 4 mm[.157 in]
Product Depth 47.5 mm
Product Length 47.5 mm
Product Height 82.5 mm
Rated Cross Section 10 mm ²
Product Spacing 10 mm[.394 in]
Usage Conditions
Storage Temperature Range -55 – 110 °C[-67 – 230 °F]
Installation Temperature Range -5 – 40 °C[23 – 104 °F]
Operating Temperature Range -55 – 110 °C[-67 – 230 °F]
Industry Standards
IP Rating IP20
UL Flammability Rating UL 94V-0



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 1SNK900002R0000 BAZ1



BAZH1

TE Pari CS-R3

TE Part # 1SNK900107R0000

TE Part # 1SNK900203R0000 TP2

























Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(318)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(30)

Customers Also Bought





TE Part #1SNK705150R0000 ZK2.5-PE



TE Part #1SNK706010R0000 ZK4



TE Part #1SNK706020R0000 ZK4-BL



TE Part #1SNK706150R0000 ZK4-PE



TE Part #1SNK708010R0000 ZK6



TE Part #1SNK708020R0000 ZK6-BL



TE Part #1SNK708150R0000 ZK6-PE



TE Part #1SNK710010R0000 ZK10



ZK16-BL



ZK16-PE

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1SNK710020R0000_B1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK710020R0000_B1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1SNK710020R0000_B1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

English

ZK10-BL

English

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Blue, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK



SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Agency Approvals

Agency Approval Document

English