

PRODUCT-DETAILS

OT800KFCC3B

OT800KFCC3B Enclosed Switch Disconnecter



Informations générales

Extension du type de produit	OT800KFCC3B
Code de produit	1SCA022303R0310
EAN	6417019078328
Description courte	OT800KFCC3B Enclosed Switch Disconnecter
Description longue	<p>Encl. Switch Disconnecter, 3-p. 415V AC23 720A, 400kW. Plastic enclosure. IP65. Black Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included.</p>

Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
Informations RoHS	1SCC340075D0201
Toxic Substances Control Act - TSCA	1SCC340095D0201

Commande

Quantité minimum	1 pièce
Code douanier	85363090
Pays d'origine	Finland (FI)

Downloads Préférés

Fiche produit, informations techniques	1SCC340015C0201
Instructions et manuels	1SCC340015M0004
Mechanical Drawings	OTPK765625P2II.stp

Dimensions

Produit Largeur Net	560 mm
Produit Hauteur Net	760 mm
Produit Longueur Net	250 mm
Poids net	17.83 kg

Technique

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 720 A (500 V) 720 A (690 V) 720 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 720 A (690 V) 720 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 720 A (500 V) 720 A (690 V) 720 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 400 kW (500 V) 500 kW (690 V) 710 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 720 A
Tension assignée de tenue aux chocs (U_{imp})	20 kV
Tension assignée d'isolement (U_i)	acc. to IEC/EN 60664-1 1000 V
Tension	Circuit principal 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 80 kA
Courant assigné de courte durée admissible (I_{cw})	for 1 s 20 kA
Rated Conditional Short-Circuit Current (I_{nc})	90 kA
Power Loss	at Rated Operating Conditions per Pole 40 W
Degré de pollution	3
Handle Color	Black

Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Normes et standards	IEC 60947-1, -3
Nombre de pôles	3
Neutral Type	Detachable neutral
Connecting Capacity Main Circuit	Hole Diameter 12 mm Screw Clamp / PE Terminal 4pc,25 ... 120 mm ²
Cable Entry Position	Top/Bottom
Cable Outlets Per Side	2xII-flange / 2xII-flange
Indice de protection	acc. to IEC 60529 IP65
Résistance aux chocs	Housing IK08
Matériau du boîtier	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Couple de serrage	Main Circuit 75 N·m

Technique UL/CSA

Couple de serrage	Main Circuit 75 N·m
-------------------	---------------------

Environnement

Statut RoHS	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	1SCC340029D2704
REACH Declaration	1SCC340076D0201

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	575 mm
Emballage Niveau 1 Longueur	780 mm

Emballage Niveau 1 Hauteur	340 mm
Emballage Niveau 1 Poids	20 kg
Emballage Niveau 1 EAN	6417019078328

Classifications

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
Catégorie DEEE	4. Large Equipment (Any External Dimension More Than 50 cm)

Catégories

Produits basse tension → Interrupteurs et appareillage à fusibles en coffret → Interrupteurs-sectionneurs en coffret → Enclosed Switch-Disconnectors

