


## LAMPE LED 230V GU10



Lampe GU10. **LED SHARP 35 000 h.** En substitution des lampes halogènes.

QPAR 16 1 LED 230V GU10 ◀ 45°-55°

P (w)	Couleur	Lumens	Teinte	Code
8	blanc	650	● 2700 K	<b>2930</b>
8	blanc	700	○ 4000 K	<b>2931</b>
8	gris	650	● 2700 K	<b>2967</b>
8	gris	700	○ 4000 K	<b>2968</b>
6	blanc	400	● 2700 K	<b>2948</b>
6	blanc	450	○ 4000 K	<b>2949</b>
6	gris	400	● 2700 K	<b>2954</b>
6	gris	450	○ 4000 K	<b>2955</b>
4	blanc	260	● 2700 K	<b>2961</b>
4	blanc	280	○ 4000 K	<b>2962</b>

LED 8	2700 K	8 W	55°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>837</b>	1,04	
2	<b>209</b>	2,1	
3	<b>93</b>	3,1	

LED 4	2700 K	4 W	45°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>367</b>	0,83	
2	<b>92</b>	1,7	
2,5	<b>59</b>	2,1	


LED 6	2700 K	6 W	45°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>576</b>	0,83	
2	<b>144</b>	1,7	
2,5	<b>92</b>	2,1	

LED 8	4000 K	8 W	55°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>861</b>	1,04	
2	<b>215</b>	2,1	
3	<b>96</b>	3,1	

LED 4	4000 K	4 W	45°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>406</b>	0,83	
2	<b>102</b>	1,7	
2,5	<b>65</b>	2,1	

LED 6	4000 K	6 W	45°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>667</b>	0,83	
2	<b>167</b>	1,7	
2,5	<b>107</b>	2,1	

La technologie des lampes LED progressant rapidement, la puissance (W) est susceptible d'être inférieure à celle indiquée tout en conservant un flux lumineux (lm) équivalent ou supérieur. Nos produits peuvent être modifiés afin de les adapter aux meilleures performances disponibles.



Lampe GU10. **LED EPISTAR 25 000 h.** En substitution des lampes halogènes.

QPAR 16 1 LED 230V GU10 ◀ 38°-40°

P (w)	Couleur	Lumens	Teinte	Code
8	blanc	580	● 3000 K	<b>2983</b>
8	blanc	710	○ 4000 K	<b>2984</b>
6	blanc	490	● 3000 K	<b>2981</b>
6	blanc	510	○ 4000 K	<b>2982</b>

LED 8E	3000 K	8 W	40°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>1192</b>	0,73	
2	<b>298</b>	1,5	
2,5	<b>191</b>	1,8	

LED 8E	4000 K	8 W	40°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>1432</b>	0,73	
2	<b>358</b>	1,5	
2,5	<b>229</b>	1,8	

LED 6E	3000 K	6 W	38°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>1105</b>	0,69	
2	<b>276</b>	1,4	
2,5	<b>177</b>	1,7	

LED 6E	4000 K	6 W	38°
h (m)	E <sub>max</sub> (lx)	d (m)	
1	<b>1144</b>	0,69	
2	<b>286</b>	1,4	
2,5	<b>183</b>	1,7	