

STRIP LED

100928.99

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor/Outdoor
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 5000mm
A: 4mm
Warranty: 5 years
Weight: 0.15kg

Tech data

Luminous flux in emergency: L min = 50 L max = 210 - 1h: 18% / 3h: 7%
IP: 65
Insulation class: III
Supply voltage: 24 Vdc
Energy efficiency class: G
SELV: No

Source

Light source: LED
Source power: 11.5W/m
Source luminous flux: 1016lm
Colour temperature: 2700K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



SMD 2216 (182 LED/m)
Biadesivo - sezionabile ogni 38,4 mm (7 LED)
Biadesive - cuttable every 38,4 mm (7 LED)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.