
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 < 2. WITHDRAL AT 0



Product designation		Selector switch actuator key - 3 position
Product type designation		LPFS37
General characteristics		
Colour		Black
Type of positions		Selector switch
Material		Aluminium and zinc alloy
IEC degree of protection		IP66, IP67 and IP69K
Mechanical features		
Mechanical life c	ycles	1000000
Fixing		Without mounting adapter
Mounting adapter		LPXAU120M
UL technical data		
UL degree of protection		Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions		
Temperature		
Operating temperature		
min	°C	-25
max	°C	+70
Storage temperature		
min	°C	-40
max Pinnersia s	°C	+85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

cULus

ETIM classification





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 < 2. WITHDRAL AT 0

ETIM 8.0

EC002611 -Control switch