

# P-30 PCB

105860.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: ADJUSTABLE  
Optics: SPOT  
Beam: 40°  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 800mm  
A: 31mm  
H: 31mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 14.9W  
Luminaire luminous flux: 1078lm  
IP: 20  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 12W  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 2 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance



CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# P-30 PCB

105860.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES


---



P-30: ANGOLO L PLAFONE-SOSP-PARETE BIA

103327.01


---



P-30: TESTATA PER INSTALL.VERT. BIA

1058D8.01


---



P-30: SNODO 3P PER PCB/STRIP BIANCO

105853.01

---



P-30: SNODO NO CAVI BIANCO

105854.01


---



P-30: COVER ANGOLO L BIANCO

103329.01

---



P-30: TESTATE PLAF/SOSP/PAR/SPOT BIA

103361.01

---




Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# P-30 PCB

105860.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



P-30: ANGOLO T PLAFONE-SOSP BIA


**103331.01**



P-30: COVER ANGOLO T BIANCO

**103333.01**

## MOUNTING ACCESSORIES




P-30: ROSONE LATER. ALIM L=1200 3P BIA

**103320.01**



P-30: CAVO DI SOSPENSIONE

**103318.99**



P-30: ROSONE CARTON. ALIM L=1200 3P BIA

**103319.01**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.