

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

CATEGORY 6A STP PLUG-TO-PLUG ZONE CORDS						
FLAMMABILITY RATING	PART NUMBERS	MIN. CABLE LENGTH**	CABLE COLOR			
	SAPLWH10M	10m (394")				
LSZH	SAPLWH20M	20m (788")				
	SAPLWH30M	30m (1182")	WHITE			
	SAPLWH40M	40m (1575")				
	SAPLWH50M	50m (1969")				
CMR	SAPRBU100	100ft (1200")	BLUE			
DUAL (CM/LSZH)	SAPDWHIOM	10m (394")				
	SAPDWH20M	20m (788")				
	SAPDWH30M	30m (1182")	WHITE			
	SAPDWH40M	40m (1575")				
	SAPDWH50M	50m (1969")				

STRAIN RELIEF BOOTS AVAILABLE IN BLACK ONLY.
**=LENGTH (SEE FIGURE 2, SHEET 1)

SAP* SERIES			N/A	
I.I. NUMBER		WORK II	NSTRUCTION	
N/A			N/A	
TX6A 1GIG S	SHIELD	ED PLUG-	TO-PLUG ZONE CORD)
	CL	JSTOMER DRA	WING	
TITEM REVISION NAME M02678BJ/00			Danmur	
DATASET FILE NAME M02678BJ	_DC10/00F	PANDUI		
UNLESS OTHERW DIMENSIONAL TOLERA	ISE SPEC ANCES AF	CIFIED, RE: IN [mm]	SEE NOTES	
.x ± .1 [2.54] .xx ± .01 [.25]	.XXX ±		SEE NOTES	
		RD ANGLE DJECTION	DRAWING NUMBER: 02678-10	
BJN 3-5-08	RJDU :	SCALE NONE	SHT 2 0F 2	SIZE

PRODUCT SPEC/PKG SPEC

PART NUMBER

02678-10

ECN

D10100DA/14

00F

REV

7-27-23

DATE

BJN

JAD0

CHK

APR

EHA | SEE SHEET 1 FOR REVISION HISTORY

DESCRIPTION