


# Product Environmental Profile

## EasyPact CVS100BS Circuit breaker, TM-D trip unit, 3P 3d





## General information

### Representative product

EasyPact CVS100BS Circuit breaker, TM-D trip unit, 3P 3d - LV510938

### Description of the product

EasyPact CVS100BS is a 3 poles 3d fixed circuit breaker with a high level of performance and cost-saving functionality. It is an optimal choice for small and medium-sized buildings protection applications.

### Functional unit

Protect during 20 years the installation against overloads and short-circuits in circuit with assigned voltage 440V and rated current 100A. This protection is ensured in accordance with the following parameters:


- Number of poles 3p
- Rated breaking capacity 25kA at 415V
- Trip unit provides an adjustable thermal overload protection and a fixed magnetic protection.



## Constituent materials

### Reference product mass

908.5 g including the product, its packaging and additional elements and accessories



Plastics	49.2%
Metals	36.4%
Others	14.4%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



## Additional environmental information

The EasyPact CVS100BS Circuit breaker, TM-D trip unit, 3P 3d presents the following relevant environmental aspects


<b>Manufacturing</b>	Manufactured at a Schneider Electric production site ISO14001 certified		
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive		
	Packaging weight is 128.5 g, consisting of paper (4%), cardboard (94%), PE (2%) Product distribution optimised by setting up local distribution centres		
<b>Installation</b>	LV510938 does not need any special installation		
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials		
	No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.		
	Recyclability potential:	<b>37%</b>	Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



## Environmental impacts

<b>Reference life time</b>	20 years			
<b>Product category</b>	Circuit-breakers			
<b>Installation elements</b>	LV510938 does not need any special installation			
<b>Use scenario</b>	Load rate: 50% of In Use time rate: 30% of RLT			
<b>Geographical representativeness</b>	Thailand			
<b>Technological representativeness</b>	EasyPact CVS100BS is a 3 poles 3d fixed circuit breaker with a high level of performance and cost-saving functionality. It is an optimal choice for small and medium-sized buildings protection applications.			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Energy model used: Thailand	Electricity mix; AC; consumption mix, at consumer; 220V; TH	Electricity mix; AC; consumption mix, at consumer; 220V; TH	Electricity mix; AC; consumption mix, at consumer; 220V; TH

Compulsory indicators		EasyPact CVS100BS Circuit breaker, TM-D trip unit, 3P 3d - LV510938					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.41E-04	2.39E-04	0*	0*	2.52E-06	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	3.00E-01	9.38E-03	5.35E-04	0*	2.90E-01	2.31E-04
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	7.92E-02	2.42E-03	1.23E-04	0*	7.66E-02	5.80E-05
Contribution to global warming	kg CO <sub>2</sub> eq	4.28E+02	3.84E+00	1.17E-01	0*	4.24E+02	9.07E-02
Contribution to ozone layer depletion	kg CFC11 eq	5.74E-06	6.04E-07	0*	0*	5.13E-06	5.52E-09
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	8.91E-02	9.96E-04	3.82E-05	0*	8.80E-02	2.44E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m <sup>3</sup>	9.12E-01	6.63E-01	0*	0*	2.49E-01	9.56E-05
Total Primary Energy	MJ	3.01E+03	1.47E+02	1.66E+00	0*	2.86E+03	1.14E+00



Optional indicators		EasyPact CVS100BS Circuit breaker, TM-D trip unit, 3P 3d - LV510938						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	2.56E+03	7.14E+01	1.65E+00	0*	2.49E+03	9.18E-01	
Contribution to air pollution	m³	2.25E+04	1.12E+03	4.99E+00	0*	2.14E+04	8.15E+00	
Contribution to water pollution	m³	8.91E+03	6.03E+02	1.93E+01	1.06E+00	8.28E+03	9.10E+00	
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Use of secondary material	kg	1.71E-01	1.71E-01	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	1.43E+02	8.47E+00	0*	0*	1.34E+02	0*	
Total use of non-renewable primary energy resources	MJ	2.86E+03	1.39E+02	1.66E+00	0*	2.72E+03	1.14E+00	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.42E+02	7.99E+00	0*	0*	1.34E+02	0*	
Use of renewable primary energy resources used as raw material	MJ	4.82E-01	4.82E-01	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.85E+03	1.26E+02	1.66E+00	0*	2.72E+03	1.14E+00	
Use of non renewable primary energy resources used as raw material	MJ	1.25E+01	1.25E+01	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Hazardous waste disposed	kg	2.83E+01	1.99E+01	0*	0*	7.07E+00	1.27E+00	
Non hazardous waste disposed	kg	2.87E+01	1.78E+00	4.16E-03	0*	2.69E+01	3.48E-03	
Radioactive waste disposed	kg	4.21E-03	7.85E-04	2.97E-06	0*	3.42E-03	5.57E-06	
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Materials for recycling	kg	4.69E-01	5.51E-02	0*	1.26E-01	0*	2.87E-01	
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	5.73E-03	0*	0*	0*	0*	5.73E-03	
Exported Energy	MJ	3.98E-04	3.61E-05	0*	3.62E-04	0*	0*	

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.4, database version 2022-01 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2210016_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	11/2023	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Validity period	5 years	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

ENVPEP2210016\_V1

© 2019 - Schneider Electric – All rights reserved

11/2023