

## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: BLACK  
Dimming: PUSH, DALI  
Emergency: NO  
L: 589x589mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 2.1kg

## Tech data

Luminaire input power: 28.5W  
Luminaire luminous flux: 1909lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 24W  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## COMPLETION ACCESSORIES


---



HERO: MOD.CIECO 250 NE

**108676.02**


---



HERO: MOD.CIECO ANG.SX 150 NE

**108677.02**

---



HERO: MOD.CIECO ANG.DX 150 NE

**108678.02**

---



HERO: MOD.CIECO 1120 NE

**108679.02**

---



HERO: MOD.CIECO 1400 NE

**108680.02**

---



HERO: MOD.CIECO 1680 NE

**108681.02**

---

## MOUNTING ACCESSORIES

---



HERO: SOSPL3000 1PZ. TESTA/CODA

**108685.99**

---



HERO: SOSPL3000 1PZ. UNIONE

**108686.99**

---



HERO: STAFFA PARETE "L" NE

**108687.02**

---



HERO: KIT INCASSO LED (1X)

**108688.99**


---



HERO: SPESS. CARTONG. 10MM 2PZ.

**108689.99**

---



KIT ALIMENTAZIONE L1200 5P BIA

**108921.01**

---



KIT ALIMENTAZIONE L1200 5P NE

**108921.02**



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**



KIT ALIMENTAZIONE L3000 5P NE

**108922.02**