

© Panduit Corp. 2017

Harness Adapter

The following information can be used to create an adapter harness to retrofit a PDM4.0 25-pin electrical interface connection as a drop-in replacement for a legacy 15-pin electrical interface connection for a generation 3.0 (PDM) dispenser.

Pin Signal	Customer EI Connector		PDM EI Connector	
	DB15 Female	PDM G3 Function	DB25 Male	PDM G4 Function
M0+	1	Remote Operation Enable (M0)	2	Remote Operation Enable (M0)
M0-	2		15	
M1+	3	Trigger (Start Cycle) (M1)	3	Trigger (Start Cycle) (M1)
M1&M2 -	4		16,17	
M2+	5	Reset (M2)	4	Reset (M2)
M3+	6	System Ready/Error (M3)	18	System Ready/Error (M3)
M3-	7		5	
M4+	8	Cycle In Process (M4)	19	Cycle In Process (M4)
M4-	9		6	
M5+	10	PDM Tie Exit Error (M5)	20	Fault code (M5)
M5-	11		7	
M6+	12	PAT Tie Entry Error (M6)	21	Fault code (M6)
M6-	13		8	
M7+	14	PDM Jammed (M7)		
M7-	15			

Reference Documentation

EI Manual PA28091A01
 Repair Manual PA28088A01
 Operation Manual PA27647A01

<p>Email: techsupport@panduit.com</p> <p>EU Website: www.panduit.com/emea</p> <p>EU Email: emeatoolservicecenter@panduit.com</p>	 www.panduit.com	<p>Technical Support Tel: 1-800-777-3300</p> <p>Panduit Europe • EMEA Service Center Almelo, Netherlands Tel: +31 546 580 452 • Fax: +31 546 580 441</p>
---	---	--