

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: NO
L: 800mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years
Weight: 1.5kg

Tech data

Luminaire input power: 14.6W
Luminaire luminous flux: 1146lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 12W
Source luminous flux: 1989lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



SCREENS



LUCKY MINI: DIFF. OPALE L=6500

103507.99



LUCKY MINI: DIFF. OPALE PER L800

103510.99

COMPLETION ACCESSORIES



4x

KIT GIUNZIONE MODULI P-30/LUCKY MINI


103317.99



LUCKY MINI: COPPIA TESTATE CAFFEA

103509.20

MOUNTING ACCESSORIES




KIT ALIMENTAZIONE L3000 5P CAF

108922.20




LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99




ALL-TRACK: COPPIA ADATT. 3P+DALI NER

106723.02



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

106723.01



KIT ALIMENTAZIONE L1200 5P CAF

108921.20