



## Features

Use: Indoor  
Type of installation: RECESSED INTO BRICKWORK, RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: TRANSPARENT  
Colour: BLACK  
Dimming: ON/OFF  
Emergency: NO  
L: 37mm  
A: 37mm  
H: 34mm  
D: 32-35mm  
Warranty: 5 years  
Weight: 0.12kg

## Tech data

Luminaire luminouse flux: 110lm  
IP: 65  
Insulation class: III  
Supply voltage: DC 700 MA

## Source

Light source: LED  
Source power: 2W  
Colour temperature: 3000K  
LED lifespan: 30000h L70 B20


## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



## MOUNTING ACCESSORIES

---




NEWSTEP: PLACCA MURALE

**109405.99**


## ELECTRICAL ACCESSORIES

---




ALIM. LED 700MA - 30W - IP20

**E907K0030KK**




ALIM. LED 350MA - 8W - IP20

**E903K0006KK**




ALIM. LED 700MA - 12W - IP20

**E907K0012KK**



ALIM. LED 350MA - 15W - IP20

**E903K0015KK**




ALIM. LED 4W/700MA 2.5-6V

**101322.99**

## DIMMABLE ACCESSORIES

---



ALIM. LED 25W 700MA/2-36V DALI/PUSH

**101336.99**