



NOTES:

1. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A LIST OF CURRENT PARTS APPLICABLE FOR USE WITH THIS PRODUCT.
2. TERMINATED WITH (8 POSITION) MODULAR PLUG ON ONE END AND A (8 POSITION) MODULAR JACK ON THE OTHER END PER THE WIRE MAP DESCRIBED IN TABLE 1.
3. CONSTRUCTED WITH 28 AWG SOLID CONDUCTOR CATEGORY 6A F/UTP HALOGEN FREE (CM/LSZH) PATCH CABLE.
4. MATERIALS:
 PLUG: POLYCARBONATE
 CONTACTS AND IDCs: GOLD PLATED PHOSPHOR BRONZE
 JACK HOUSING: ABS
5. NOMINAL CABLE DIAMETER: 0.185IN [4.7]
6. CABLE JACKET COLOR: GREEN
7. WEIGHT: 0.44LB/10 PCS [198g/ 10 PCS]
8. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIALS RESTRICTIONS OF RoHs, (EUROPEAN DIRECTIVE 2011/65/EU ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHs TECHICAL ADAPTATION COMMITTEE.

TABLE 1: WIRING SCHEME

PLUG		JACK	
WIRED TO THE T568 'B' WIRING SCHEME			
POSITION	CONDUCTOR COLOR	POSITION	CONDUCTOR COLOR
1	WHITE/ORANGE	1	CONDUCTOR CUT
2	ORANGE	2	CONDUCTOR CUT
3	WHITE/GREEN	3	ORANGE
4	BLUE	4	WHITE/BLUE
5	WHITE/BLUE	5	CONDUCTOR CUT
6	GREEN	6	WHITE/GREEN
7	WHITE/BROWN	7	CONDUCTOR CUT
8	BROWN	8	CONDUCTOR CUT

PART NUMBER		MA017	
TITLE			
CATEGORY 6, PDU YOST SERIAL DATA CABLE		ASSEMBLY	
CUSTOMER DRAWING			
ITEM REVISION NAME		00266NAA/00	
DATASET FILE NAME		00266NAA_DC02/00A	
		THIRD ANGLE PROJECTION	
MATERIAL		SEE NOTE 4	
DRAWING NUMBER		00266NAA-02	
REV	DATE	BY	CHK
R	5-8-18	BJN	DCS
DESCRIPTION		ECN	
RELEASED TO PRODUCTION		00266NAA-02	
REV	DATE	BY	CHK
DESCRIPTION		ECN	
DRAWN BY	DATE	CHK	SCALE
BJN	5-8-18	DCS	NONE
SHEET 1 OF 1		A	

A-SIZE CUSTOMER