



V3DU3-020RM25A

Ruler3000

3D MACHINE VISION

SICK
Sensor Intelligence.



Ordering information

| Type | Part no. |
|----------------|----------|
| V3DU3-020RM25A | 1132219 |

Other models and accessories → www.sick.com/Ruler3000



Detailed technical data

Features

| | |
|--|---|
| Task | 3D inspection Measuring, 3D |
| Technology | 3D triangulation |
| Product category | Streaming, pre-calibrated |
| Shutter technology | Global-Shutter |
| Working distance | 245.5 mm ... 370.5 mm |
| Example field of view | 190 mm x 50 mm |
| Exposure mode | Linear HDR |
| Illumination | Integrated |
| Illumination color | Red, laser, Visible, 660 nm, ± 15 nm |
| Laser class | 2 (EN 60825-1:2014+A11:2021; IEC 60825-1:2014, Complies with the FDA performance requirements for laser products except for conformance with IEC 60825-1 Ed.3., as described in Laser Notice 56 dated May 8, 2019.) |
| Data synchronization | Free running, encoder triggered, external triggering |
| Factory calibrated | ✓ |
| 3D measurement | ✓ |
| Scatter measurement | ✓ |
| Reflectance measurement | ✓ |
| Ambient light suppression | ✓ ¹⁾ |
| Scheimpflug adapter, integrated | ✓ |

¹⁾ Red bandpass filter.

| | |
|--|--------|
| Width at minimum operating distance | 155 mm |
| Width at maximum operating distance | 220 mm |
| Maximum height range | 125 mm |

¹⁾ Red bandpass filter.

Mechanics/electronics

| | |
|-------------------------------|---|
| Connection type | Voltage – I/O: M12, 17-pin male connector Gigabit Ethernet: M12, 8-pin female connector, X-coded |
| Connector material | M12: Nickel-coated brass |
| Supply voltage | 24 V DC, $\pm 10\%$ |
| Ripple | $< 5 V_{pp}$ |
| Power consumption | $\leq 12 W$ |
| Current consumption | $\leq 1.5 A$ |
| Enclosure rating | IP65 IP67 |
| Protection class | III |
| Housing material | Aluminum |
| Housing color | Blue |
| Window material | PMMA |
| Weight | 1.8 kg |
| Dimensions (L x W x H) | 245 mm x 65 mm x 108 mm |

Performance

| | |
|----------------------------|---|
| Image sensor | CMOS sensor from SICK with ROCC technology, M30 |
| Scan/frame rate | 46,000 3D profiles/s, In reduced ROI 7,000 3D profiles/s, full format |
| Data points/profile | 3,200 |
| Repeatability | $3.9 \mu m$ ¹⁾ |
| Typical resolution | Z resolution (height): $8 \mu m \dots 16 \mu m$, X resolution (width): $65 \mu m \dots 92 \mu m$ |

¹⁾ Height values measured for different positions in the field of view. 20 measurements are performed at each position. The repeatability value is the 3-fold of the standard deviation (3σ) for all measurements at all positions.

Interfaces

| | |
|-------------------------------|--|
| Ethernet | ✓, UDP/IP |
| Data transmission rate | $\leq 1 Gbit/s$ |
| Configuration software | Stream Setup |
| Operating system | Windows 10 |
| Programming interface | GenAPI, GenTL, Proprietary SICK GenIStream |
| Inputs/outputs | 4 x HIGH = 10 V ... 28.8 V, configurable |
| Encoder interface | RS-422 5 V, 2 x HTL single-ended |

Ambient data

| | |
|-------------------|-------------------------|
| Shock load | 15 g, 3 cycles per axis |
|-------------------|-------------------------|

¹⁾ Non-condensing.

²⁾ Height values measured for different positions in the field of view. 20 measurements are performed at each position. The repeatability value is the 3-fold of the standard deviation (3σ) for all measurements at all positions.

| | |
|--------------------------------------|--------------------------------------|
| Vibration load | 5 g, 10 Hz ... 150 Hz (EN 60068-2-6) |
| Ambient operating temperature | 0 °C ... +50 °C ¹⁾ |
| Storage temperature | -30 °C ... +70 °C ¹⁾ |
| Depth precision | 3.9 µm ²⁾ |


¹⁾ Non-condensing.

²⁾ Height values measured for different positions in the field of view. 20 measurements are performed at each position. The repeatability value is the 3-fold of the standard deviation (3 σ) for all measurements at all positions.

Classifications

| | |
|-----------------------|----------|
| ECLASS 5.0 | 27310205 |
| ECLASS 5.1.4 | 27310205 |
| ECLASS 6.0 | 27310205 |
| ECLASS 6.2 | 27310205 |
| ECLASS 7.0 | 27310205 |
| ECLASS 8.0 | 27310205 |
| ECLASS 8.1 | 27310205 |
| ECLASS 9.0 | 27310205 |
| ECLASS 10.0 | 27310205 |
| ECLASS 11.0 | 27310205 |
| ECLASS 12.0 | 27310205 |
| ETIM 5.0 | EC001820 |
| ETIM 6.0 | EC001820 |
| ETIM 7.0 | EC001820 |
| ETIM 8.0 | EC001820 |
| UNSPSC 16.0901 | 43211731 |

Dimensional drawing (Dimensions in mm (inch))




- ① Optical receiver (center)
- ② Optical sender (center)
- ③ Threaded mounting hole (M5, 12 mm deep) with through hole (Ø 4.2 mm)
- ④ Power I/O connection
- ⑤ Connector Gigabit Ethernet (Gig E)
- ⑥ Threaded mounting hole (M5, 9 mm deep)
- ⑦ Position and alignment hole for locating pins (Ø 5 mm)

Field of view


Ruler3020

Guaranteed field of view in mm




Characteristic curve



Width of the field of view via the Z position



Z resolution via Z position



X resolution via Z position






The maximum line rate is based on the number of sensor lines used

- ① Line rate (kHz)
- ② Number of lines
- ③ Ruler3000 with activated HDR
- ④ Ruler3000 without activated HDR
- ⑤ Bandwidth limit for image width 2,560, height range only
- ⑥ Bandwidth limit for image width 3,072, height range only
- ⑦ Bandwidth limit for image width 2,560, height range and reflectance
- ⑧ Bandwidth limit for image width 3,072, height range and reflectance

Recommended accessories

Other models and accessories → www.sick.com/Ruler3000

| | Brief description | Type | Part no. |
|---|---|--------------------|----------|
| Mounting brackets and plates | | | |
|  | Mounting bracket set consisting of mounting bracket, cooling plate, includes angle display for setting the tilt angle | Mounting bracket | 2076735 |
| Plug connectors and cables | | | |
|  | <ul style="list-style-type: none"> • Connection type head A: Female connector, M12, 17-pin, straight, A-coded • Connection type head B: Flying leads • Signal type: Sensor/actuator cable, serial, CANopen, digital I/Os • Cable: 3 m, 17-wire, PUR • Description: Sensor/actuator cable, serial, CANopen, digital I/Os, twisted pair, shielded • Application: Drag chain operation | YF2A2D-030UV1XLEAX | 6042772 |
|  | <ul style="list-style-type: none"> • Connection type head A: Male connector, M12, 8-pin, straight, X-coded • Connection type head B: Male connector, RJ45, 8-pin, straight • Signal type: Ethernet, Gigabit Ethernet • Cable: 2 m, 8-wire, PUR, halogen-free • Description: Ethernet, Gigabit Ethernet, shielded • Application: Zones with oils and lubricants | YM2X18-020EG1MRJA8 | 2106258 |

Recommended services

Additional services → www.sick.com/Ruler3000

| | Type | Part no. |
|--|--|----------|
| Extended warranty | | |
| <ul style="list-style-type: none"> • Product area: Identification solutions, machine vision, Detection and ranging solutions, safety camera sensors, Safety laser scanners, Safety radar sensors • Range of services: The services correspond to the scope of the statutory manufacturer warranty (SICK general terms of delivery). • Duration: Five-year warranty from delivery date. | Extended warranty for a total of five years from delivery date | 1680671 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com