



LFR-XXFFBI2HAKX

LFR SicWave

FREE-SPACE RADAR

SICK
Sensor Intelligence.



Illustration may differ



Ordering information

| Type | Part no. |
|-----------------|----------|
| LFR-XXFFBI2HAKX | 6074399 |

Other models and accessories → www.sick.com/LFR_SicWave

Detailed technical data

Features

| | |
|----------------------------|---|
| Medium | Fluids |
| Measurement | Continuous |
| Probe type | Flange with encapsulated antenna system |
| Frequency band | W-band (within 75 ... 85 GHz) |
| Measuring range | Up to 25 m (82.02 ft) |
| Angle of dispersion | 6° ¹⁾ |
| Process pressure | -1 bar ... 20 bar (-100 kPa ... 2,000 kPa / -14.5 psig ... 290.1 psig) |
| Process temperature | -40 °C ... +130 °C |
| RoHS certificate | ✓ |
| HART | ✓ |
| Indication | Installed |
| Control element | Bluetooth Magnet pin operation |

¹⁾ Outside the specified aperture angle, the level of the radar signal energy is lowered by 50% (-3 dB).

Performance

| | |
|---|---|
| Accuracy of sensor element | ≤ 1 mm ¹⁾ |
| Non-repeatability | ≤ 1 mm |
| Digital measurement resolution | < 1 mm |
| Analog measurement resolution | 0.3 μA |
| Digital output temperature drift | ≤ 3 mm / 10 K, max. 10 mm |
| Current output temperature drift | ≤ 0.03% / 10 K relating to the 16 mA span or ≤ 0.3% |
| Deviation on current output due to digital-analog conversion | < 15 μA |
| Measurement cycle time | Approx. 700 ms |

¹⁾ Measurement distance > 0.25 m / 0.8202 ft.

²⁾ Time span after abrupt change to the measurement distance by max. 2 m for bulk material applications until the output signal has assumed 90% of its steady-state value for the first time (IEC 61298-2).

| | |
|---------------------------|-----------------------------|
| Step response time | $\leq 3 \text{ s}^{2)}$ |
| MTBF | $3,37 \cdot 10^6 \text{ h}$ |
| Display | ✓ |

¹⁾ Measurement distance > 0.25 m / 0.8202 ft.

²⁾ Time span after abrupt change to the measurement distance by max. 2 m for bulk material applications until the output signal has assumed 90% of its steady-state value for the first time (IEC 61298-2).

Electronics

| | |
|---------------------------------|--|
| Supply voltage | 12 V DC ... 35 V DC, 18 V DC ... 35 V DC with illumination switched on ¹⁾ |
| Protection class | III (IEC 61010-1) |
| Connection type | M20 x 1.5 / cable gland nickel-plated brass (ø5 mm - 9 mm) |
| Output signal | 4 mA ... 20 mA / HART ²⁾ |
| Contamination rating | 4 |
| Enclosure rating | IP66 / IP68 |
| EMC | EN 61326-1 |
| Start-up current | < 3.6 mA |
| Overvoltage category | III (IEC 61010-1) |
| Short-circuit protection | ✓ |

¹⁾ All connections are polarity protected. All outputs are overload and short-circuit protected.

²⁾ Range of the output signal: 3.8 mA ... 20.5 mA / HART (factory setting); fault current < 3.6 mA or 22 mA.

Mechanics

| | |
|-------------------------------|--|
| Process connection | Flange DN 50 PN 40 form C, DIN 2501 / 316L |
| Housing material | Aluminum |
| Housing design | Single-chamber housing |
| Sealing material | PTFE |
| Antenna material | PTFE |
| Second line of defense | Not integrated |

Ambient data

| | |
|--------------------------------------|-------------------|
| Ambient operating temperature | -40 °C ... +80 °C |
| Ambient temperature, storage | -40 °C ... +80 °C |

Classifications

| | |
|---------------------|----------|
| ECLASS 5.0 | 27200505 |
| ECLASS 5.1.4 | 27200505 |
| ECLASS 6.0 | 27200505 |
| ECLASS 6.2 | 27200505 |
| ECLASS 7.0 | 27200505 |
| ECLASS 8.0 | 27200505 |
| ECLASS 8.1 | 27200505 |
| ECLASS 9.0 | 27200505 |
| ECLASS 10.0 | 27270807 |
| ECLASS 11.0 | 27270807 |

| | |
|-----------------------|----------|
| ECLASS 12.0 | 27274501 |
| ETIM 5.0 | EC001447 |
| ETIM 6.0 | EC001447 |
| ETIM 7.0 | EC001447 |
| ETIM 8.0 | EC001447 |
| UNSPSC 16.0901 | 41111950 |

Type code

Type code

Certification

| | |
|----|---|
| XX | Without certification |
| AC | ATEX II 1G, 1/2G, 2G Ex ia IIC T6...T1, Ga, Ga/Gb, Gb, EU-type examination no.: KIWA 20ATEX0039 X |
| AE | ATEX II 1/2G, 2G Ex db IIC T6...T1, Ga/Gb, Gb, EU-type examination no.: KIWA 20ATEX0040 X |
| IC | IEC Ex ia IIC T6...T1, Ga, Ga/Gb, Gb, EU-type examination no.: IECEx KIWA 20.0014X |
| IE | IEC Ex db IIC T6...T1, Ga/Gb, Gb, EU-type examination no.: IECEx KIWA 20.0015X |

Antenna version/second line of defense

| | |
|---|---|
| B | With plastic horn antenna |
| T | Thread with integrated horn antenna |
| U | Thread with integrated horn antenna with second line of defense |
| F | Flange with encapsulated antenna system |
| G | Flange with encapsulated antenna system with second line of defense |
| H | Hygiene connection with encapsulated antenna system |

Process connection/Material

| | |
|----|---|
| XX | Without process connection |
| XC | Mounting clamp, length: 170 mm/316L |
| XD | Mounting clamp, length: 300 mm/316L |
| TA | Thread G 3/4 PN20, DIN3852-A/316L |
| TB | Thread 3/4" NPT PN20, ASME B1.20.1/316L |
| TC | Thread G 1 1/2, PN20, DIN3852-A/316L |
| TD | Thread 1 1/2 NPT, PN20, ASME B1.20.1/316L |
| FB | Flange DN 50 PN40 Form C, DIN2501/316/316L |
| FH | Flange DN 80 PN40 Form C, DIN2501/316/316L |
| FL | Flange DN 100 PN16 Form C, DIN2501/316/316L |
| FS | Flange DN 150 PN16 Form C, DIN2501/316/316L |
| GI | Flange 2" 150 lb RF, ASME B16.5/316/316L |
| GM | Flange 3" 150 lb RF, ASME B16.5/316/316L |
| GP | Flange 4" 150 lb RF, ASME B16.5/316/316L |
| CA | Clamp 2" PN16 (Ø 64 mm) DIN32676, ISO2825/316L |
| RA | Milk pipe connection DN50; PN16; DIN11851; 316L |

Material/seal/process temperature

| | |
|---|--|
| C | Antenna material PP, seal PP, process temperature 40...+80 °C |
| I | Antenna material PTFE, seal PTFE, process temperature -40...+130 °C |
| J | Antenna material PTFE, seal PTFE, process temperature -40...+200 °C |
| W | Antenna material PTFE, seal PTFE, process temperature -196...+200 °C |
| A | Antenna material PEEK, seal FKM (SHS FPM 70C3 GLT) and PP, process temperature -40...+130 °C |
| B | Antenna material PEEK, seal FKM (SHS FPM 70C3 GLT) and PP, process temperature -40...+200 °C |


Cable entry/connection

| | |
|---|--|
| B | Round connector, M12x1 pin assignment B |
| M | M20x1.5/cable gland, PA black (Ø 5-9 mm), standard |
| 2 | M20x1.5/cable gland, nickel-plated brass (Ø 5-9 mm) |
| O | M20x1.5/cable gland, nickel-plated brass (Ø 6-12 mm) |
| J | 1/2 NPT/cable gland, PA black (Ø 5-9 mm) |
| P | 1/2 NPT/cable gland, nickel-plated brass (Ø 6-12 mm) |

Electronics

| | |
|---|----------------------------|
| H | Two-wire, 4 ... 20 mA/HART |
|---|----------------------------|

Housing/enclosure rating



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com