

PRODUCT-DETAILS

P9PLNVDR

P9PLNVDR LED block



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | P9PLNVDR |
| Code de produit | 1SFA197004R1011 |
| EAN | 7320500523759 |
| Description courte | P9PLNVDR LED block |
| Description longue | <p>The P9PLNVDR LED block is: Modular metal - LED block - Permanent - Red - Illuminated - Front mounting - 24 V ACDC</p> <p>This LED block is part of ABB's modular metal range designed for mining, construction and heavy industry applications, combining the highest reliability with the full flexibility of a modular range.</p> |

Commande

| | |
|------------------|------------|
| Quantité minimum | 10 pièce |
| Code douanier | 8539500000 |

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 1SFC151007C02_ |
| Instructions et manuels | 1SFC151011M0201 |

Dimensions

| | |
|----------------------|----------|
| Produit Largeur Net | 9.8 mm |
| Produit Hauteur Net | 39.5 mm |
| Produit Longueur Net | 56 mm |
| Poids net | 0.002 kg |

Technique

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation -30 ... 70 °C Storage -40 ... +70 °C |
| Couleur | Red |
| Voyant | Illuminated |
| Type de lampe | 24 VACDC, Integrated LED |
| Fonction | Permanent |
| Type de montage | Front mounting |
| Indice de protection | Terminals IP20 |
| Degré de pollution | 3 |
| Fréquence assignée (f) | 50 / 60 Hz |
| Tension | 24 V ACDC V |
| Connecting Capacity | Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ² |
| Type de raccordement | Screw Clamp |
| Type de borne | Screw Terminals |
| Couple de serrage | 0.9 N·m |
| Wire Stripping Length | 8 mm |

Technique UL/CSA

| | |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA | 2x 18...14 AWG |

Environnement

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006479 |
| Informations RoHS | 2CMT2019-005862 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| WEEE B2C / B2B | Business To Business |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificats et Déclarations (Numéro de document)

| | |
|-------------------------------------|---------------------|
| Certificat BV | 2CMT2019-005867 |
| CB Certificate | 2CMT2019-005874 |
| CQC Certificate | CQC2019010304237361 |
| Certificat CSA | 2CMT2019-005868 |
| Certificat ecULus | 2CMT2019-005868 |
| Declaration of Conformity - CCC | 2020980304001528 |
| Déclaration de Conformité - CE | 2CMT2019-005862 |
| Declaration of Conformity - UKCA | 2CMT2020-006121 |
| DNV GL Certificate | 2CMT2019-005876 |
| Certificat RINA | 2CMT2019-005866 |
| Certificat UL | 2CMT2019-005868 |

Emballage

| | |
|--------------------------------|---------------|
| Emballage Niveau 1 Unités | bag 1 pièce |
| Emballage Niveau 1 Largeur | 120 mm |
| Emballage Niveau 1 Longueur | 50 mm |
| Emballage Niveau 1 Hauteur | 180 mm |
| Emballage Niveau 1 Poids | 0.002 kg |
| Emballage Niveau 1 EAN | 7320500523759 |

Classifications

| | |
|---|--|
| ETIM 7 | EC000204 - Lamp holder block for control circuit devices |
| ETIM 8 | EC000204 - Lamp holder block for control circuit devices |
| eClass | V11.0 : 27371209 |
| UNSPSC | 39122221 |
| Code de catégorie granulaire IDEA (IGCC) | 5219 >> Switch part or accessory |
| E-Number (Finland) | 2314961 |

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Modular Metal Range P9M

