# 1SET315111R0000 - ACTIVE

#### ENTRELEC | M12 Connector

TE Internal #: 1SET315111R0000 M12 Pigtail Cable Assembly, 5 Position, 4 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF

#### View on TE.com >

#### Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies



M8/M12 Application Type: Industrial Fieldbus

Industrial Protocols: DeviceNet

Number of Positions: 5

Keying Code: A

Connector Type (End A): M12 Socket

## Features



#### Product Type Features

LED	Without
Product Type	Cable Assembly
Cable Type	PVC
Assembly Type	Overmolded
Connector Type (End A)	M12 Socket
Cable Assembly Type	M12 Pigtail
Configuration Features	
Number of Positions	5
Keying Code	A
Electrical Characteristics	
Operating Voltage	60 VDC
Body Features	
Cable Exit Angle	Right Angle
Environmental Protection	IP67

### 1SET315111R0000

M12 Pigtail Cable Assembly, 5 Position, 4 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



Conductor Material	Copper Alloy
Connector Color	Black
Cable Jacket Color	Gray
Contact Features	
Contact Current Rating	4 A
Nechanical Attachment	
Connector Orientation (End A)	Right Angle
Housing Features	
Housing Material	PA66+25GF
Dimensions	
Overall Outside Cable Diameter	7.1 mm
Wire Size	22 – 24 AWG
Operation/Application	
M8/M12 Application Type	Industrial Fieldbus
Shielded	Yes
ndustry Standards	
Industrial Protocols	DeviceNet
Packaging Features	
Packaging Method	Bag
Packaging Quantity	5
Other	
Cable Assembly Length	4 m
Cable Assembly Configuration	Single Ended
Product Compliance For compliance documentation, visit the product page on TE.com>	
ELL Dalle Directive 2011// E/ELL	
EU RoHS Directive 2011/65/EU EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Compliant with Exemptions Restricted Materials Above Threshold
Shind Rons 2 Directive With Order NO 52, 2010	Restricted matchais Above Theallold

## 1SET315111R0000

M12 Pigtail Cable Assembly, 5 Position, 4 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



Halogen ContentNot Low Halogen - contains Br or Cl > 900ppm.

Solder Process Capability

Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## **Compatible Parts**



## Also in the Series | M12 Connector



### Documents

Product Drawings M12A5-FR-PVC-4.0M

English

CAD Files

**C** For support call+1 800 522 6752

### 1SET315111R0000

M12 Pigtail Cable Assembly, 5 Position, 4 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



#### 3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_1SET315111R0000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SET315111R0000\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SET315111R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages Infographic - entrelec ews-linecard English

Catalog - ENTRELEC-M8-M12-RJ45

English

Product Specifications Application Specification

English