

PRODUCT-DETAILS

SBS/U10.0.1-885

SBS/U10.0.1-885 HVAC-Slave-device, 10f CE, black matt



Informations générales

Extension du type de produit	SBS/U10.0.1-885
Code de produit	2CKA006330A0049
EAN	4011395298831
Description courte	SBS/U10.0.1-885 HVAC-Slave-device, 10f CE, black matt

Description longue

Freely configurable multifunction control element. Room temperature control/Controller extension with max. 10gang control With labelling field. Transparent labelling sheet with standard symbols included in delivery. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function). With integrated temperature sensor. With actual value temperature display With display of set-value temperature. The bus can be connected via enclosed terminal block. With integrated KNX bus coupler. Number of bus subscribers: 1

Installation

Instructions et manuels	2CKA000073BB9649
-------------------------	------------------

Technique

Fiche produit, informations	No document needed
-----------------------------	--------------------

techniques

Nombre de LED	1
Maximum Number of Switching Outputs	33
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Design Range	tenton
Type de montage	Flush Mounted Surface Mounted
Finition de surface	Lacquered Matt
Matériau	Thermoplastic
RAL Number	RAL 9005 - Noir foncé
Couleur	black matt
Poids de la batterie	0 g
Application Function	Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	2CKA200000E7872
REACH Declaration	2CKA309999E9999
Classe de température par défaut	I
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	90.1 mm
Produit Hauteur Net	167.1 mm
Produit Longueur Net	44.2 mm
Poids net	352.5 g
Profondeur d'encastrement (t ₂)	30.7 mm

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E4129
--------------------------------	-----------------

Classifications

ETIM 8	EC001101 - Room temperature controller for bus system
ETIM 9	EC001101 - Room temperature controller for bus system
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	9032 10 20
eClass	V11.0 : 27143133

Catégories

Produits basse tension → Home and Building Automation → KNX → User Operation → ABB-Tenton® → 10 fold

