





THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
P34D41M-XXYZ	SEE SHEET 2



**SPECIFICATION:**

**1. STANDARD:**

UNIT TYPE:	MONITORED INPUT
ORIENTATION:	VERTICAL, 0U FULL
OUTLET QTY&TYPE:	(28) C13, (6) C19
INPUT VOLTAGE:	200-240VAC
INPUT CURRENT:	32A
BREAKER QTY&TYPE:	(2) 16AMP, SINGLE-POLE
INPUT PHASE:	SINGLE-PHASE
RATED POWER:	7.4kVA
INPUT PLUG:	IEC 60309 2P+E 6H 32A
INPUT POWER CORD:	SEE SHEET 2 FOR PART NUMBER TABLE
REGULATORY STANDARD:	RoHS COMPLIANT

**2. ADDITIONAL:**

NONE

**3. ACCESSORIES:**


(1) QUICK-START GUIDE

**NOTES:**


1. PRIMARY DIMENSIONS ARE IN MILLIMETERS. SECONDARY DIMENSION ARE IN [ INCHES ]
2. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES
3. VISIT OUR ON-LINE CATALOG AT [WWW.PANDUIT.COM](http://WWW.PANDUIT.COM) FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
4. FOR FULL PRODUCT FUNCTIONALITY REFER TO USER MANUAL
5. DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP END FED" CONFIGURATION

**IDENTIFICATION**

FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE SHEET 2 CONFIGURABLE PART NUMBERS: P34D41M-XX Y Z



BOTTOM VIEW



**PLUG/RECEPTACLE BLOCK**



PLUG  
IEC 60309, 2P 3W, 6H  
IP44 (SPLASHPROOF)  
32A, 200-250V MAX RATED INPUT



RECEPTACLES  
IEC 60320/C19  
16A, 250V MAX RATED OUTPUT



RECEPTACLES  
IEC 60320/C13  
10A, 250V MAX RATED OUTPUT

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO INCLUDE CONFIGURABLE OPTION 'DE-CODER'	P34D41M
01B	12/14/2017	GEORGE	MIM	EDM	UPDATED DESCRIPTION	P34D41M
01A	07/27/2017	GEORGE	MIM	EDM	INITIAL RELEASE	P34D41M

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.		SIGN
		DATE
		PRINT
TITLE INTELLIGENT SERIES PDU P34D41M-XXYZ CUSTOMER DRAWING		
ITEM REVISION NAME:		
DATASHEET FILE NAME:		
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR:
Tolerance(mm) 0<L<50 ±0.5 50<L<250 ±1.0 250<L<500 ±1.5 500<L<1000 ±2.5 1000<L<2000 ±4.0		N/A
THIRD ANGLE PROJECTION		DRAWING NUMBER: P34D41M_DC
DRAWN BY GEORGE	DATE 07/27/2017	SCALE NONE
CHK SEAN	SHT 1 OF 2	
		SCALE B

2



1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P34D41M	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-BL1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-BL1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-RD1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-RD1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-RD1C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-WH1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-WH1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-WH1C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-YL1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-YL1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-YL1C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-BU1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-BU1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-BU1C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-GN1A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-GN1B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-GN1C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-BL2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-BL2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-BL2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-RD2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-RD2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-RD2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-WH2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-WH2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-WH2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-YL2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-YL2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-YL2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-BU2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-BU2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-BU2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg
P34D41M-GN2A	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3'[+3.5"/-1.75"]	5.9kg
P34D41M-GN2B	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5'[+7"/-3.5"]	6.2kg
P34D41M-GN2C	VERTICAL,(28) C13,(6)C19,MONITORED INPUT, 200-240V/32A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10'[+10"/-5"]	6.5kg

B

B

A

A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO INCLUDE CONFIGURABLE OPTION 'DE-CODER'	P34D41M
01B	12/14/2017	GEORGE	MIM	EDM	UPDATED DESCRIPTION	P34D41M
01A	07/27/2017	GEORGE	MIM	EDM	INITIAL RELEASE	P34D41M

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.		SIGN
		DATE
		PRINT
TITLE INTELLIGENT SERIES PDU P34D41M-XYZ CUSTOMER DRAWING		
ITEM REVISION NAME:		<b>PANDUIT</b>
DATASHEET FILE NAME:		
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR: N/A
 THIRD ANGLE PROJECTION		DRAWING NUMBER: P34D41M_DC
DRAWN BY	DATE	SCALE
GEORGE	07/27/2017	NONE
CHK	SCALE	SHT 2 OF 2
SEAN	NONE	B

2



1