

Product designation				Switch disconnectors
Product type designation				GLD...UL
Number of poles		Nr.	4	
Operating voltage type				DC
Contact characteristics				
IEC Conventional free air thermal current I _{th}		A	100	
Rated insulation voltage U _i IEC/EN		V	1500	
Operating current I _e	DC21B			
		600V	A	100
		800V	A	100
		1000V	A	100
		1200V	A	100
		1500V	A	100
DCPV1				
		Operating current I _e 600V	A	100
		Operating current I _e 800V	A	100
		Operating current I _e 1200V	A	100
		Operating current I _e 1500V	A	100
DCPV1				
		600V	A	100
		800V	A	100
		1200V	A	100
		1500V	A	100
UL98B				
		1000V	A	100
		1500V	A	100
Mechanical features				
Operating position		normal allowable		Vertical plan Any
Fixing				Screw / DIN rail 35mm
Terminals		type		M8 x 25
Tightening torque for terminals		min	Nm	15
		max	Nm	22
		min	lbin	132
		max	lbin	194
Conductor section		IEC min	mm ²	70
		IEC max	mm ²	185
		AWG/kcmil min		00
		AWG/kcmil max		400
Ambient conditions				
Operating temperature		min	°C	-25
		max	°C	+55
Storage temperature		min	°C	-40
		max	°C	+70

Max altitude	m	3000
Resistance & Protection		
Pollution degree		3
ETIM classification		
ETIM 8.0		EC000216 - Switch disconnecter