




Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
A: Ø40mm
H: 60mm
D: 35mm
Warranty: 5 years
Weight: 0.075kg

Tech data

Luminaire luminous flux: 308lm
Luminous flux in emergency: 1h: 78% / 3h: 32%
IP: 20
Insulation class: III
Supply voltage: DC 500 mA
SELV: No



Source

Light source: LED
Source power: 5W
Colour temperature: 2700K
CRI: >90
LED lifespan: 30000h

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

ELECTRICAL ACCESSORIES




ALIM. LED MAX 18W 500MA

101325.99




ALIM. LED MAX 20W 500MA

101309.99



ALIM. LED 15W/500MA


101307.99



ALIM. LED 14W 500MA/2-27V


101331.99

DIMMABLE ACCESSORIES




ALIM. MAX.20W/500MA DALI/PUSH/0-10/1-10

101904.99



ALIM. LED MAX 10W 500MA DALI PUSH


101316.99



ALIM. LED 25W 500MA/2-50V DALI/PUSH


101334.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99