

Features

Use: Indoor
 Type of installation: WALL, SUSPENDED, CEILING MOUNTED
 Emission: DIRECT
 Optics: OPAL
 Colour: WHITE
 Dimming: ON/OFF
 Emergency: NO
 L: 800mm
 A: 800mm
 H: 81mm
 Made in: ITALY
 Warranty: 5 years
 Weight: 12.6kg

Tech data

Luminaire input power: 69.7W
 Luminaire luminous flux: 8007lm
 IP: 40
 Insulation class: I
 Supply voltage: 220-240V 50/60Hz
 SELV: No

Source

Light source: LED
 Source power: 63W
 Source luminous flux: 10794lm
 Colour temperature: 4000K
 CRI: >80
 Colour tolerance: 3 Step MacAdam
 LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

MOUNTING ACCESSORIES



ROTO: ALIMENTAZIONE L1200 3P. BIA

104423.01



ROTO: ALIMENTAZIONE L3000 3P. BIA.

104425.01



ROTO: D=800 KIT 4 SOSP. L3000

104428.99
