

Part number

CHIN 24



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "104.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 104.27
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	98,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163101
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Packaging length	250,00 mm
Packaging height	145,00 mm
Packaging width	300,00 mm
Packaging weight	1,96 kg
Packaging volume	10,88 dm ³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747187626
Sub-packaging weight	0,49 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187633

Part number CHIN 24



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" LS-TYPE version

<p>inserts: page</p> <p>CD 64 poles + @ 51+53 *</p> <p>CT, CTS **) 64 poles + @ 57 *</p> <p>CDD 108 poles + @ 64+66 *</p> <p>CDE 46 poles + @ 83+85 *</p> <p>CSH 24 poles + @ 91+93 *</p> <p>CCE 24 poles + @ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS 24 poles + @ 122+123 *</p> <p>CTE, CTSE **) 24 poles + @ 129 *</p> <p>CMSE 10+2 (aux) poles + @ 139 *</p> <p>CMCE 10+2 (aux) poles + @ 138 *</p> <p>CX 4/8 poles + @ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with double lever</p>	<p> hoods with 4 pegs</p>																			
<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">description</td> <td style="width: 35%;">part no.</td> <td style="width: 35%;">entry</td> </tr> <tr> <td>bulkhead mounting housing, with 2 levers</td> <td>CHIN 24</td> <td>M</td> </tr> <tr> <td>surface mounting housing, high construction, with 2 levers</td> <td>MAPN 24.32</td> <td>32</td> </tr> </table>	description	part no.	entry	bulkhead mounting housing, with 2 levers	CHIN 24	M	surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">part no.</td> <td style="width: 35%;">entry</td> </tr> <tr> <td>MHON 24.32</td> <td>32</td> </tr> <tr> <td>MFON 24.32</td> <td>32</td> </tr> <tr> <td>MHVN 24.32</td> <td>32</td> </tr> <tr> <td>MFVN 24.32</td> <td>32</td> </tr> </table>	part no.	entry	MHON 24.32	32	MFON 24.32	32	MHVN 24.32	32	MFVN 24.32	32
description	part no.	entry																			
bulkhead mounting housing, with 2 levers	CHIN 24	M																			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32																			
part no.	entry																				
MHON 24.32	32																				
MFON 24.32	32																				
MHVN 24.32	32																				
MFVN 24.32	32																				
<p>**) only in the CHIN 24 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <div style="text-align: center;"> <p>IP65</p> </div> <p>dimensions shown are not binding and may be changed without notice</p>	<p>dimensions in mm</p> <p>CHIN 24</p> <p>MAPN 24.32</p>	<p>dimensions in mm</p> <p>MFON 24.32</p> <p>MFVN 24.32</p> <p>MHON 24.32</p> <p>MHVN 24.32</p>																			

Notes

Dimensions shown in mm are not binding and may be changed without notice.