

MODÈLES À ANSE ISOLÉE

Anse recouverte de PVC rouge isolant.

Référence	↑ mm	Anse ∅ mm	Couleur	Masse g
AL-260- (*)	50	6,2	●	200
AL-260-00	50	6,2	●	200
AL-260-Z	50	6,2	●	200
AL-260-S- (**)	70	6,2	●	210
AL-260-S-00	70	6,2	●	210
AL-260-S-Z	70	6,2	●	210
AL-260-(**)-EX	50	6,2	●	200
AL-260-00-EX	50	6,2	●	200
AL-260-Z-EX	50	6,2	●	200
AL-260-S-(**)-EX	70	6,2	●	210
AL-260-S-00-EX	70	6,2	●	210
AL-260-S-Z-EX	70	6,2	●	210

(*) Ajouter les numéros de clé au choix (Autres numéros sur commande spéciale) : 111 - 1 111 - 222 - 2 222 - 333 - 3 333 - 444 - 4 444 - 555 - 5 555 - 666 - 6 666 - 777 - 7 777 - 888 - 8 888 - 999 - 9 999.

(**) Ajouter les numéros de clé 111 ou 222 seulement.

LES ⊕

- Isolé 1000V AC.
- Marquage sur les 2 faces : texte en français ou symbole normalisé / Identification de l'utilisateur



Masse



↑ mm Hauteur totale



∅ Diamètre