

Product designation				Rotary cam switches
Product type designation				GX16
General characteristics				
Switching diagram				92
N° of elements				2
Options				Enlarged front plate
Contact characteristics				
Rated insulation voltage U_i	IEC/EN	V	690	
	UL/CSA	V	600	
Rated impulse withstand voltage U_{imp}			kV	6
Conventional free air thermal current I_{th}	IEC/EN	A	16	
	UL/CSA	A	12	
Rated operational voltage			V	440
Maximum fuse size for short-circuit protection I_n (gG)	10kA	A	20	
	25kA	A	16	
Rated short time current I_{cw}			1s	A
				250
Operational current I_e IEC/EN	AC1/AC21A			
			A	16
AC15	110V		A	10
	220/230V		A	8
	380/400V		A	4
	660/690V		A	3
Rated operational power in AC	Three-phase AC-3			
	220/230V		kW	3.5
	380/440V		kW	4.5
	500/690V		kW	5.5
	Single-phase AC-3			
	110V		kW	0.55
	220/230V		kW	1.5
	380/440V		kW	2.2
	Three-phase AC23A			
	220/230V		kW	3.7
	380/440V		kW	6.5
	500/690V		kW	7.5
Single-phase AC23A	110V		kW	0.75
	220/230V		kW	1.8
	380/440V		kW	3
Rated operational current in DC	DC21A			
	48V		A	16
	60V		A	16
	110V		A	4
	220V		A	0.5

	440V	A	0.25
DC23A (poles in series)	24V	A	16 (1)
	48V	A	16 (2)
	60V	A	16 (3)
	110V	A	10 (3)
	220V	A	7 (4)
DC13	24V	A	16
	48V	A	14
	60V	A	12
	110V	A	0.8
	220V	A	0.3
	440V	A	0.15

Mechanical features

Terminals screw			3M
Tightening torque for terminals max		Nm	0.5

Conductor size

AWG - Rigid cable

min	AWG	20
Max	AWG	14

AWG - Flexible cable

min	AWG	20
Max	AWG	14

Conductor size (IEC) - Flexible cable

min	mm ²	0.5
Max	mm ²	2.5

Conductor size (IEC) - Rigid cable

min	mm ²	0.5
Max	mm ²	2.5

Mechanical life		cycles	5x10 ⁶
-----------------	--	--------	-------------------

UL technical data

Motor power for direct-on-line control

for three-phase motor

120V	HP	1.5
240V	HP	3
480V	HP	5
600V	HP	5

for single-phase motor

120V	HP	0.75
240V	HP	1

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree		IP65
Terminals IP degree		IP20

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete