


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. APPLICATION TOOLS - GS4MT, PPTMT, ST2MT, ST3MT, HTMT
2. MINIMUM LOOP TENSILE STRENGTH - 200 LBS. [889 NEWTONS]
WHEN TESTED ON A 1.5" MANDREL.
3. BRACKETS [] DENOTE DIMENSIONS IN MILLIMETERS
AND ARE SHOWN FOR REFERENCE ONLY
4. TOLERANCES:
 .XXX = ±.010 [.25]
 .XX = ±.02 [.5]
 .X = ±.03 [.8]
 ANGLES = ±2°
5. MATERIAL: 316 STAINLESS STEEL

PANDUIT PART NO.	MAX BUNDLE DIAMETER	PACKAGE QTY	LENGTH L=±.3 [7]
MLT1S-CP316	1" [25]	100	5.0" [127]
MLT2S-CP316	2" [51]	100	7.9" [201]
MLT2.75-CP316	2.7" [69]	100	10.2" [259]
MLT4S-CP316	4" [102]	100	14.3" [362]
MLT6S-CP316	6" [152]	100	20.5" [521]
MLT8S-CP316	8" [203]	100	26.8" [679]
MLT10S-CP316	10" [254]	100	33.0" [838]



REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
12	04.14.16	JBN	SKB	RGRO	D. REVISED DIMENSION & ADDED TOLERANCE RANGE	N41120BS_DC
11	04.13.16	BDK	SKB	RGRO	C. REMOVED TOLERANCES FROM TITLE BLOCK; SEE NOTE 4 B. MADE DIMENSION 3 PLACES	N41120BS_DC
10	10.09.15	BDK	SKB	RGRO	A. ADDED NEW TIP CONFIGURATION	N41120BS_DC
09A	3/13	JAMB	MIM	RGRO	UPDATE DRAWING TO NEW GLOBAL PANDUIT TITLE BLOCK WITH PANDUIT LOGO	SSECN01037
08A	2/12	MIM	RGRO	---	NOTE:#3 METRIC DIMENSIONS NOTED AS BEING SHOWN FOR REFERENCE ONLY	----

TITLE						
METAL LOCKING TIE STANDARD SERIES 316 STAINLESS STEEL						
CUSTOMER DRAWING						
ITEM REVISION NAME		N41120BS/12				
DATASET FILE NAME		N41120BS_DC/12A				
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]						PANDUIT MATERIAL: 316 STAINLESS STEEL DRAWING NUMBER: N41120BS_DC
.X ±		.XXX ±				
.XX ±		ANGLES ±				
THIRD ANGLE PROJECTION						
DRAWN BY	DATE	CHK	SCALE			
JAMB	2/12	DPN	2:1	SHT 1 OF 1		
						SIZE A