

## **NOTES UNLESS OTHERWISE SPECIFIED:**

PANDUIT TOOL NUMBER PTS INSTALLS: SM, M, I, AND S CABLE TIE CROSS-SECTIONS. THIS PNEUMATIC TOOL TIGHTENS CABLE TIES AND CUTS OFF EXCESS PORTION WHEN PRESET IS ATTAINED.

CABLE TIE CROSS-SECTION CODE: SM = SUBMINIATURE, M = MINIATURE, I = INTERMEDIATE, S = STANDARD

**TOOL WEIGHT = 17.3 OZ. (490 GRAMS)** 

PNEUMATIC REQUIREMENTS = 70 - 90 PSIG FILTERED NON-LUBRICATED AIR AND EXTERNAL PNEUMATIC HOSE

	_	_	_		_		_	_
_	_	_	_	$\boldsymbol{-}$	_	N		_

**KGTSBLD – BLADE REPLACEMENT KIT** 

**KPTSTL - TENSION LOCKING KIT** 

PPH10 – EXTERNAL PNEUMATIC HOSE:

1/8" NPT FEMALE QUICK DISCONNECT SOCKET. AND 1/8" NPT MALE QUICK DISCONNECT FITTING.

PHCA - EXTERNAL PNEUMATIC HOSE: 1/8" NPT FEMALE QUICK DISCONNECT SOCKET. AND

1/4" NPT MALE QUICK DISCONNECT FITTING.


PL289N1 – FILTER/REGULATOR

WB24468D01 – BLADE GUARD HOUSING

## **DIMENSIONS SHOWN IN (PARENTHESES) ARE METRIC:**

A = 2.37	( 60.19)	TRIGGER SPAN
B = 9.42	(239.27)	OVERALL LENGTH
C = 6.38	(162.05)	OVERALL HEIGHT
D = .060/.066	(1.52/1.68)	<b>BLADE GUARD SLOT WIDTH</b>
E = 0.74	( 18.79)	<b>BLADE GUARD HEIGHT</b>
F = 0.55	( 13.97)	BLADE GUARD WIDTH
G = 0.90	( 22.86)	SELECTOR KNOB
H = 1.34	( 34.04)	TOOL WIDTH

PNEUMATIC HOOK UP: ATTACH FEMALE QUICK DISCONNECT SOCKET END OF PNEUMATIC HOSE TO MALE QUICK DISCONNECT FITTING AT END OF PTS TOOL.



## **SEE SHEET 1 FOR PICTORAL**

CORP. TINLEY PARK, ILLINOIS	IDUI'	Pan									
JSTOMER DRAWING	CUST	PTS									
AND E DRO JECTION											
NONE	MATL:	DRAWN BY:									
SHEET DRAWING NO.		DATE:	ON	RMATI	IFO	ATED IN	VING REVISION & RELA	RDRAV	1 FOF	E SHEET	SE
WB24652A01		CHK'D:	SUP	CUST	-R	ECN	DESCRIPTION	CHK'D	BY	DATE	REV

**UNLESS OTHERWISE** CIFIED. ALL DIMENSIONS **GIVEN IN INCHES, THIRD** ANGLE PROJECTION.

DWG Α SIZE